



CARTON STAPLER & SPEED NAILER

- AT-3103A** 32mm crown air carton stapler (nail length:18mm)
AT-3103B 32mm crown air carton stapler (nail length:22mm)
AT-3104A 35mm crown air carton stapler (nail length:18mm)
AT-3104B 35mm crown air carton stapler (nail length:22mm)



Features	Application
1. Efficient 2. Saving energy 3. Easy to operate and hand carry 4. The tightness and penetration depth of staple is adjustable	For fast and secure closing of transport packaging, such as folding boxes, overlap cartons, board wrappings and similar packaging.

- HT-3103A** 32mm crown manual drive carton stapler (nail length:18mm)
HT-3103B 32mm crown manual drive carton stapler (nail length:22mm)
HT-3104A 35mm crown manual drive carton stapler (nail length:18mm)
HT-3104B 35mm crown manual drive carton stapler (nail length:22mm)



Features	Application
1. Efficient 2. Saving energy 3. Easy to operate and hand carry 4. The tightness and penetration depth of staple is adjustable	For fast and secure closing of transport packaging, such as folding boxes, overlap cartons, board wrappings and similar packaging.

AT-3100 Air speed nailer



AT-3110 Air speed hammer



Model No.	Fastener				Tool Specification								Magazine Capacity
	Crown (mm)	Thickness (mm)	Width (mm)	Length (mm)	Length		Height		Weight		Pressure		
					mm	inch	mm	inch	kg	lb	psi	kg/cm²	
AT-3103A	32	0.9	1.9	15 & 18	400	15.7	200	7.9	2.0	4.4	70-100	5-7	100
AT-3103B	32	0.9	1.9	22	400	15.7	200	7.9	2.0	4.4	70-100	5-7	100
AT-3104A	35	0.9	2.2	15 & 18	400	15.7	200	7.9	2.0	4.4	70-100	5-7	100
AT-3104B	35	0.9	2.2	22	400	15.7	200	7.9	2.0	4.4	70-100	5-7	100
HT-3103A	32	0.9	1.9	15 & 18	460	18.1	310	12.2	1.67	3.68	-	-	100
HT-3103B	32	0.9	1.9	22	460	18.1	310	12.2	1.67	3.68	-	-	100
HT-3104A	35	0.9	2.2	15 & 18	460	18.1	310	12.2	1.67	3.68	-	-	100
HT-3104B	35	0.9	2.2	22	460	18.1	310	12.2	1.67	3.68	-	-	100

Model No.	Blow per min. (BPM)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-3100	1000	4.7	120	1/4"	3/8"	5	140	2.69	1.22	90	6.3	10/Ctn/14 kg/0.8'	2
AT-3110	1000	4.0	100	1/4"	3/8"	5	140	2.20	1.00	90	6.3	10/Ctn/12 kg/0.8'	2