

AIR IMPACT SCREWDRIVER (PISTOL TYPE)

AT-4071
Air impact screwdriver



AT-4077
Air impact screwdriver



AT-4078
Air impact screwdriver



AT-4079
Air impact screwdriver



AT-4175
Air impact screwdriver



AT-4176
Air impact screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4071	1/4	6.35	1/4	6~8	10000	65	88	6.10	155	1/4"	3/8"	7.5	212	3.04	1.38	90	6.3	10/Ctn/17 kg/1.3'	2
AT-4077	1/4	6.35	1/4	6~8	8000	70	95	6.10	155	1/4"	3/8"	12.0	340	2.51	1.14	90	6.3	10/Ctn/13 kg/0.6'	3
AT-4078	1/4	6.35	5/16	8~10	8000	85	115	6.38	162	1/4"	3/8"	12.0	340	2.56	1.16	90	6.3	10/Ctn/13 kg/0.6'	3
AT-4079	1/4	6.35	3/8	10	7500	100	136	6.54	185	1/4"	3/8"	12.0	340	2.60	1.18	90	6.3	10/Ctn/14 kg/0.6'	3
AT-4175	1/4	6.35	5/16	8	9500	80	108	6.10	155	1/4"	3/8"	9.0	255	3.13	1.42	90	6.3	10/Ctn/16 kg/1.26'	3
AT-4176	1/4	6.35	1/2	12	12000	140	190	5.71	145	1/4"	3/8"	10.0	283	3.13	1.60	90	6.3	10/Ctn/17.5 kg/0.83'	3

AIR IMPACT SCREWDRIVER (PISTOL TYPE)

AT-4069
Air impact screwdriver



AT-4171
Air impact screwdriver



AT-4174
Composite air impact screwdriver



AT-4074
Air impact screwdriver



AT-4076
Air impact screwdriver



AT-4172B
Air impact screwdriver



AT-4068
Air impact screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4068	1/4	6.35	3/16	4~5	10000	30	41	6.10	155	1/4"	3/8"	7	198	1.98	0.90	90	6.3	15/Ctn/16kg/1.3'	2
AT-4069	1/4	6.35	1/4	6~8	7000	50	68	7.09	180	1/4"	3/8"	7	198	2.64	1.20	90	6.3	10/Ctn/14kg/0.9'	2
AT-4074	1/4	6.35	3/16	4~5	11000	30	41	6.10	155	1/4"	3/8"	7	198	1.98	0.90	90	6.3	15/Ctn/16kg/1.3'	2
AT-4076	1/4	6.35	1/4	5~6	8500	40	54	6.93	176	1/4"	3/8"	9	255	2.53	1.15	90	6.3	10/Ctn/13.9kg/1.2'	2
AT-4171	1/4	6.35	5/16	8	7700	80	108	7.68	195	1/4"	3/8"	7	198	2.87	1.30	90	6.3	10/Ctn/15kg/0.9'	2
AT-4172B	1/4	6.35	3/16	4~5	10000	30	41	6.10	155	1/4"	3/8"	7	198	1.96	0.89	90	6.3	10/Ctn/11kg/0.7'	2
AT-4174	1/4	6.35	3/16	5	16000	40	55	7.28	185	1/4"	3/8"	9	255	1.76	0.88	90	6.3	10/Ctn/11kg/0.9'	2

AIR IMPACT SCREWDRIVER (STRAIGHT TYPE)

AT-4165
Air impact screwdriver



AT-4166
Air impact screwdriver



AT-4167
Air impact screwdriver



AT-4161
Air impact screwdriver



AT-4263
Air impact screwdriver



AT-4264
Air impact screwdriver



AT-4170
Air impact screwdriver



AT-4070A
Air impact screwdriver



AT-4060A
Air impact screwdriver



AT-4060
Air impact screwdriver



AT-4067
Angle impact screwdriver



AT-4262
Angle impact screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4060	1/4	6.35	3/16	4~5	11000	25	34	7.00	178	1/4"	5/16"	5.0	142	1.54	0.70	90	6.3	20/Ctn/16kg/1.1'	2
AT-4060A	1/4	6.35	3/16	4~5	11000	25	34	7.28	185	1/4"	5/16"	5.0	142	1.59	0.72	90	6.3	20/Ctn/16kg/1.1'	2
AT-4067	1/4	6.35	3/16	5	6500	30	41	10.24	260	1/4"	5/16"	7.3	207	3.20	1.45	90	6.3	20/Ctn/31kg/1.4'	2
AT-4070A	1/4	6.35	1/4	6	7000	50	68	8.86	220	1/4"	5/16"	7.5	212	2.34	1.06	90	6.3	20/Ctn/25kg/1.1'	2
AT-4161	1/4	6.35	5/16	6~8	9500	60	81	6.50	165	1/4"	5/16"	8.5	241	2.30	1.05	90	6.3	20/Ctn/25kg/1.72'	2
AT-4165	1/4	6.35	3/16	5	9000	25	34	7.17	182	1/4"	5/16"	6.0	170	1.65	0.75	90	6.3	20/Ctn/20kg/0.85'	2
AT-4166	1/4	6.35	1/4	6	8000	55	75	7.83	199	1/4"	5/16"	7.0	198	2.09	0.95	90	6.3	20/Ctn/24kg/0.85'	2
AT-4167	1/4	6.35	5/16	8	8000	65	88	7.87	200	1/4"	5/16"	7.0	198	2.18	0.99	90	6.3	20/Ctn/25kg/0.85'	2
AT-4170	1/4	6.35	5/16	8	8000	80	108	8.07	205	1/4"	5/16"	7.0	198	2.20	1.00	90	6.3	20/Ctn/25kg/1.1'	2
AT-4262	1/4	6.35	3/16	4~5	7500	20	27.1	9.17	233	1/4"	5/16"	6.0	170	2.69	1.22	90	6.3	20/Ctn/26 kg /1.9'	2
AT-4263	1/4	6.35	1/4	6~8	8500	70	95	9.06	230	1/4"	5/16"	7.0	198	2.62	1.19	90	6.3	20/Ctn/27Kg/0.88'	2
AT-4264	1/4	6.35	5/16	8	8500	85	115	9.06	230	1/4"	5/16"	7.0	198	2.67	1.21	90	6.3	20/Ctn/27Kg/0.88'	2

CUSHION CLUTCH AIR SCREWDRIVER



AT-4184

External adjustable clutch
air screwdriver (2500rpm)



AT-4083

External adjustable clutch
air screwdriver (1800rpm)



AT-4084

External adjustable clutch
air screwdriver (800rpm)



AT-4181

External adjustable clutch
air screwdriver (2400rpm)



AT-4086

Adjustable clutch
air screwdriver (1800rpm)



AT-4087

Adjustable clutch
air screwdriver (800rpm)



AT-4080

Adjustable clutch
air screwdriver (1800rpm)



AT-4080A

Adjustable clutch
air screwdriver (800rpm)



AT-4182

Adjustable clutch
air screwdriver (1800rpm)



AT-4183

Adjustable clutch
air screwdriver (800rpm)



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		in-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4080	1/4	6.35	3/16	5	1800	45-115	5.1~13	8.27	210	1/4"	3/8"	12.0	340	2.51	1.14	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4080A	1/4	6.35	1/4	6	800	45-145	5.1~16.4	8.86	225	1/4"	3/8"	12.0	340	2.91	1.32	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4083	1/4	6.35	3/16	5	1800	22-80	2.5~9	8.86	225	1/4"	3/8"	9.5	269	2.82	1.28	90	6.3	10/Ctn/14Kg/1'	3
AT-4084	1/4	6.35	3/16	5	800	22-106	2.5~12	9.61	244	1/4"	3/8"	9.5	269	3.15	1.43	90	6.3	10/Ctn/15Kg/1'	3
AT-4086	1/4	6.35	3/16	5	1800	45-115	5.1~13	8.27	210	1/4"	3/8"	12.0	340	2.56	1.16	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4087	1/4	6.35	1/4	6	800	45-145	5.1~16.4	9.25	230	1/4"	3/8"	12.0	340	2.91	1.32	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4181	1/4	6.35	3/16	5	2400	106	12.0	8.66	220	1/4"	3/8"	6.5	184	2.64	1.20	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4182	1/4	6.35	3/16	5	1800	45-115	5.1~13	7.68	195	1/4"	3/8"	10.0	283	2.65	1.20	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4183	1/4	6.35	1/4	6	800	45-145	5.1~16.4	8.27	210	1/4"	3/8"	10.0	283	2.98	1.35	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4184	1/4	6.35	1/4	6	2500	150	17.0	8.34	212	1/4"	3/8"	10.0	283	2.38	1.08	90	6.3	10/Ctn/13Kg/0.91'	3

CUSHION CLUTCH AIR SCREWDRIVER

AT-4057
External adjustable clutch
air screwdriver (800rpm)



AT-4058
External adjustable clutch
air screwdriver (800 rpm)



AT-4059
External adjustable clutch
air screwdriver (1400 rpm)



AT-4151
External adjustable clutch
air screwdriver (800 rpm)



AT-4152
External adjustable clutch
air screwdriver (1400 rpm)



AT-4053
External adjustable clutch
air screwdriver (1800rpm)



AT-4054
External adjustable clutch
air screwdriver (800rpm)



AT-4051A
Cushion clutch air screwdriver



AT-4050 Clutch air screwdriver
AT-4050A Clutch air screwdriver



AT-4085
Cushion clutch air screwdriver



AT-4052
Cushion clutch angle air screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		in-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4050	1/4	6.35	1/8	3	1700	30	3.4	9.25	235	1/4"	1/4"	5.5	156	1.34	0.61	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4050A	1/4	6.35	1/8	3	1700	30	3.4	9.25	235	1/4"	1/4"	5.5	156	1.34	0.61	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4051A	1/4	6.35	5/32	4	1800	36	4	8.66	220	1/4"	1/4"	4.5	127	1.37	0.62	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4052	1/4	6.35	5/32	4	1600	36	4	9.25	230	1/4"	1/4"	5.0	142	1.68	0.76	90	6.3	20/Ctn/19Kg/1.4'	1.5
AT-4053	1/4	6.35	3/16	5	1800	22-71	2.5~8	10.43	265	1/4"	3/8"	8.2	232	2.51	1.14	90	6.3	20/Ctn/24Kg/1.4'	2
AT-4054	1/4	6.35	3/16	5	800	22-97	2.5~11	11.14	283	1/4"	3/8"	8.2	232	2.69	1.22	90	6.3	20/Ctn/26Kg/1.4'	2
AT-4057	1/4	6.35	3/32	2.5	800	26	3	8.90	226	1/4"	1/4"	4.0	113	1.68	0.76	90	6.3	20/Ctn/17Kg/1.1'	1.5
AT-4058	1/4	6.35	5/32	4	800	44	5	10.98	279	1/4"	1/4"	5.0	141	2.14	0.97	90	6.3	20/Ctn/22Kg/1.4'	1.5
AT-4059	1/4	6.35	5/32	4	1450	44	5	10.98	279	1/4"	1/4"	5.0	141	2.14	0.97	90	6.3	20/Ctn/22Kg/1.4'	1.5
AT-4085	1/4	6.35	3/16	5	1800	115	13	10.43	265	1/4"	3/8"	10.0	283	2.56	1.16	90	6.3	10/Ctn/14Kg/0.6'	2
AT-4151	1/4	6.35	5/32	4	800	62	7	13.15	334	1/4"	1/4"	5.0	141	2.76	1.25	90	6.3	10/Ctn/16Kg/0.8'	1.5
AT-4152	1/4	6.35	5/32	4	1400	62	7	13.15	334	1/4"	1/4"	5.0	141	2.76	1.25	90	6.3	10/Ctn/16Kg/0.8'	1.5

AIR SHUT-OFF CLUTCH SCREWDRIVER



AT-4110

Straight type lever to start shut-off air screwdriver
(800 rpm)

AT-4111

Straight type lever to start shut-off air screwdriver
(1450 rpm)



AT-4112

Pistol type shut-off air screwdriver
(800 rpm)

AT-4113

Pistol type shut-off air screwdriver
(1450 rpm)



AT-4114

Angle type shut-off air screwdriver
(800 rpm)

AT-4115

Angle type shut-off air screwdriver
(1450 rpm)



AT-4010

Push to start shut-off air screwdriver
(750 rpm)

AT-4011

Push to start shut-off air screwdriver
(2500 rpm)



AT-4010H

Push to start shut-off air screwdriver
(750 rpm)

AT-4011H

Push to start shut-off air screwdriver
(2500 rpm)



AT-4013

Push to start shut-off air screwdriver
(1000 rpm)



AT-4014

Push to start shut-off air screwdriver
(950 rpm)

AT-4015

Push to start shut-off air screwdriver
(650 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4010	5/32	4	2	2500	1.8~3.1	0.2~0.35	7.00	178	1/4"	1/4"	4.0	113	0.77	0.35	90	6.3	10/Ctn/7Kg/0.9'	1.5
AT-4010H	1/4	6.35	2	2500	1.8~3.1	0.2~0.35	7.28	185	1/4"	1/4"	4.0	113	0.55	0.25	90	6.3	20/Ctn/8Kg/0.9'	1.5
AT-4011	5/32	4	2.5	750	3.1~8.9	0.35~1.0	7.48	190	1/4"	1/4"	4.0	113	0.82	0.37	90	6.3	10/Ctn/7Kg/0.9'	1.5
AT-4011H	1/4	6.35	2.5	750	3.1~8.9	0.35~1.0	7.60	192	1/4"	1/4"	4.0	113	0.60	0.27	90	6.3	20/Ctn/8.5Kg/0.9'	1.5
AT-4013	1/4	6.35	3.5	1000	10.6~19.5	1.2~2.2	9.02	229	1/4"	1/4"	5.0	142	1.56	0.71	90	6.3	20/Ctn/14Kg/1.4'	2
AT-4014	1/4	6.35	4~5	950	17.7~42.5	2.0~4.8	9.84	250	1/4"	1/4"	5.5	156	2.05	0.93	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4015	1/4	6.35	5~6	650	26.6~62	3.0~7.0	9.84	250	1/4"	1/4"	5.5	156	2.05	0.93	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4110	1/4	6.35	4	800	14.2~27.5	1.6~3.1	11.22	285	1/4"	1/4"	7.0	198	2.09	0.95	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4111	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	11.22	285	1/4"	1/4"	7.0	198	2.09	0.95	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4112	1/4	6.35	4	800	14.2~27.5	1.6~3.1	7.68	195	1/4"	1/4"	7.0	198	2.16	0.98	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4113	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	7.68	195	1/4"	1/4"	7.0	198	2.16	0.98	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4114	1/4	6.35	5	800	19.5~38.1	2.2~4.3	13.39	340	1/4"	1/4"	7.0	198	2.69	1.22	90	6.3	10/Ctn/14Kg/1.2'	2
AT-4115	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	13.39	340	1/4"	1/4"	7.0	198	2.69	1.22	90	6.3	10/Ctn/14Kg/1.2'	2

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

AIR SHUT-OFF CLUTCH SCREWDRIVER PISTOL TYPE



AT-4016P15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016P11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017P16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017P09

Shut-off clutch air screwdriver (900 rpm)



AT-4018P17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4018P11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4018P07

Shut-off clutch air screwdriver (700 rpm)



AT-4019P17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4019P11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4019P07

Shut-off clutch air screwdriver (700 rpm)

AT-4019P05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016P15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	8.4	214	1/4"	1/4"	5	142	1.54	0.7	70	5.0	2
AT-4016P11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	8.4	214	1/4"	1/4"	5	142	1.54	0.7	70	5.0	2
AT-4017P16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	8.2	209	1/4"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4017P09	1/4	6.35	M3	900	9.7~18	1.1~2.1	8.2	209	1/4"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4018P17	1/4	6.35	M3	1700	8.8~25	1~2.8	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018P11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018P07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4019P17	1/4	6.35	M4	1700	17.6~38	2~4.3	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P07	1/4	6.35	M5	700	26.4~70	3~8	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P05	1/4	6.35	M6	550	26.4~96	3~10.9	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / PUSH START



AT-4016S15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016S11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017S16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017S09

Shut-off clutch air screwdriver (900 rpm)



AT-4018S17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4018S11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4018S07

Shut-off clutch air screwdriver (700 rpm)



AT-4019S17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4019S11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4019S07

Shut-off clutch air screwdriver (700 rpm)

AT-4019S05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016S15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	8.5	216	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4016S11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	8.5	216	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4017S16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	9	229	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4017S09	1/4	6.35	M3	900	9.7~18	1.1~2.1	9	229	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4018S17	1/4	6.35	M3	1700	8.8~25	1~2.8	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018S11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018S07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4019S17	1/4	6.35	M4	1700	17.6~38	2~4.3	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019S11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019S07	1/4	6.35	M5	700	26.4~70	3~8	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019S05	1/4	6.35	M6	550	26.4~96	3~10.9	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / LEVER START



AT-4016L15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016L11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017L16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017L09

Shut-off clutch air screwdriver (900 rpm)



AT-4018L17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4018L11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4018L07

Shut-off clutch air screwdriver (700 rpm)



AT-4019L17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4019L11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4019L07

Shut-off clutch air screwdriver (700 rpm)

AT-4019L05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016L15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	9.29	236	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4016L11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	9.29	236	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4017L16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	9.61	244	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4017L09	1/4	6.35	M3	900	9.7~18	1.1~2.1	9.61	244	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4018L17	1/4	6.35	M3	1700	8.8~25	1~2.8	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018L11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018L07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4019L17	1/4	6.35	M4	1700	17.6~38	2~4.3	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L07	1/4	6.35	M5	700	26.4~70	3~8	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L05	1/4	6.35	M6	550	26.4~96	3~10.9	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER ANGLE TYPE



AT-4016A15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016A11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017A16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017A09

Shut-off clutch air screwdriver (900 rpm)



AT-4018A17

Shut-off clutch air screwdriver (1,700 rpm)

AT-4018A11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4018A07

Shut-off clutch air screwdriver (700 rpm)



AT-4019A11

Shut-off clutch air screwdriver (1,100 rpm)

AT-4019A07

Shut-off clutch air screwdriver (700 rpm)

AT-4019A05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016A15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	11.18	284	1/8"	1/4"	5	142	0.88	0.4	70	5.0	2
AT-4016A11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	11.18	284	1/8"	1/4"	5	142	0.88	0.4	70	5.0	2
AT-4017A16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	11.46	291	1/8"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4017A09	1/4	6.35	M3	900	9.7~18	1.1~2.1	11.46	291	1/8"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4018A17	1/4	6.35	M3	1700	8.8~25	1~2.8	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018A11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018A07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4019A11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019A07	1/4	6.35	M5	700	26.4~70	3~8	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019A05	1/4	6.35	M6	550	26.4~96	3~10.9	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2

CORDLESS SHUT-OFF WRENCH / SCREWDRIVER

Brushless Motor

PT-4010P06
PT-4010P09
PT-4010P12



PT-4010A15
PT-5010A15
PT-5010A20



PT-5010A30
PT-5010A35



PTBC-18
Battery charger

Input: 100~240 VAC
Output: 18 VDC
for Li-ion



PTBP-1825
Li-ion battery pack
(18V 2.5 A.h)



FEATURES :

- Brushless motor – remarkable cycle time of longer life, accompany with maintenance free.
- Precise torque control – compliance with screwdriver according to ISO5393, CMK > 1.67 at ±10%
- Easy torque adjusting and setting system.
- High performance Lithium-ion battery pack – low self-discharge, also no memory effect.

SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Drive Size inch	Volt. V	Free Speed RPM	Capacity Bolt Size mm	MAX. Torque N-m	Overall Length mm	Net Weight w/o Battery		Net Weight W/ Battery		Noise Level (dBA)	Vibration m/s ²
							lbs	kgs	lbs	kgs		
PT-4010P06	1/4" Hex.	18V	900	M3~M5	1~6	190	2.05	0.93	2.93	1.33	<75	<2.5
PT-4010P09	1/4" Hex.	18V	700	M3~M5	1.5~9	190	2.05	0.93	2.93	1.33	<75	<2.5
PT-4010P12	1/4" Hex.	18V	500	M4~M6	2~12	190	2.05	0.93	2.93	1.33	<75	<2.5
PT-4010A15	1/4" Hex.	18V	450	M4~M6	4~15	445	2.84	1.29	3.72	1.69	<75	<2.5
PT-5010A15	3/8" Sq.	18V	450	M4~M6	4~15	445	2.84	1.29	3.72	1.69	<75	<2.5
PT-5010A20	3/8" Sq.	18V	360	M5~M6	6~20	445	2.84	1.29	3.72	1.69	<75	<2.5
PT-5010A30	3/8" Sq.	18V	260	M6~M8	12~30	530	3.72	1.69	4.61	2.09	<75	<2.5
PT-5010A35	3/8" Sq.	18V	200	M6~M8	15~35	530	3.72	1.69	4.61	2.09	<75	<2.5