

ANGLE HEAD DRILL



AT-4520A
90° angle head air drill-0.3HP, 4500 rpm
AT-4521A
90° angle head air drill-0.3HP, 3200 rpm



AT-4520B
45° angle head air drill-0.3HP, 4500 rpm
AT-4521B
45° angle head air drill-0.3HP, 3200 rpm



AT-4520C
360° offset angle head air drill-0.3HP, 4500 rpm
AT-4521C
360° offset angle head air drill-0.3HP, 3200 rpm



AT-4522A
90° angle head air drill-0.45HP, 4200 rpm
AT-4523A
90° angle head air drill-0.45HP, 2800 rpm



AT-4522B
45° angle head air drill-0.45HP, 4200 rpm
AT-4523B
45° angle head air drill-0.45HP, 2800 rpm



AT-4522C
360° offset angle head air drill-0.45HP, 4200 rpm
AT-4523C
360° offset angle head air drill-0.45HP, 2800 rpm



TP-4520A
90° angle head



TP-4520B
45° angle head



TP-4520C
360° offset angle head



- Motor housing milled from solid bar for precision motor alignment.
- Motor cylinder & rotor are hardened alloy steel to ensure proper alignment and long life.
- Smooth quiet operation.

SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Free Speed RPM	Threaded Drill Bits	Power		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
			hp	W	inch	mm			scfm	l/min	lb	kg		
AT-4520A	4500	1/4"-28	0.30	225	10.24	260	1/4"	3/8"	8	226	1.81	0.82	20/Ctn/18.2Kg/0.8'	2
AT-4520B	4500	1/4"-28	0.30	225	10.71	272	1/4"	3/8"	8	226	1.81	0.82	20/Ctn/18.2Kg/0.8'	2
AT-4520C	4500	1/4"-28	0.30	225	10.55	268	1/4"	3/8"	8	226	2.03	0.92	20/Ctn/21.8Kg/1.3'	2
AT-4521A	3200	1/4"-28	0.30	225	10.24	260	1/4"	3/8"	8	226	1.81	0.82	20/Ctn/18.2Kg/0.8'	2
AT-4521B	3200	1/4"-28	0.30	225	10.71	272	1/4"	3/8"	8	226	1.81	0.82	20/Ctn/18.2Kg/0.8'	2
AT-4521C	3200	1/4"-28	0.30	225	10.55	268	1/4"	3/8"	8	226	2.03	0.92	20/Ctn/21.8Kg/1.3'	2
AT-4522A	4200	1/4"-28	0.45	335	10.71	272	1/4"	3/8"	9	255	1.92	0.87	20/Ctn/19.2Kg/0.8'	2
AT-4522B	4200	1/4"-28	0.45	335	11.18	284	1/4"	3/8"	9	255	1.92	0.87	20/Ctn/20.6Kg/1.3'	2
AT-4522C	4200	1/4"-28	0.45	335	11.00	280	1/4"	3/8"	9	255	2.14	0.97	20/Ctn/22.8Kg/1.3'	2
AT-4523A	2800	1/4"-28	0.45	335	10.71	272	1/4"	3/8"	9	255	1.92	0.87	20/Ctn/19.2Kg/0.8'	2
AT-4523B	2800	1/4"-28	0.45	335	11.18	284	1/4"	3/8"	9	255	1.92	0.87	20/Ctn/20.6Kg/1.3'	2
AT-4523C	2800	1/4"-28	0.45	335	11.00	280	1/4"	3/8"	9	255	2.14	0.97	20/Ctn/22.8Kg/1.3'	2

3/8" AIR DRILL

AT-4330
2800 rpm 3/8" Air drill



AT-4331R
2000 rpm 3/8" Reversible air drill



AT-4332
5600 rpm 3/8" Air drill



AT-4333
2600 rpm 3/8" Air drill



AT-4334R
2800 rpm 3/8" Reversible air drill



AT-4135
2300 rpm 3/8" Air drill
AT-4237
3000 rpm 3/8" air drill



AT-4136
2300 rpm 3/8" Reversible air drill
AT-4237R
3000 rpm 3/8" Reversible air drill



AT-4130
2300 rpm 3/8" Air drill
AT-4130S
2300 rpm 3/8" Air drill with keyless chuck



AT-4131
2300 rpm 3/8" Reversible air drill
AT-4131S
2300 rpm 3/8" Reversible air drill with keyless chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4130(S)	3/8	10	2300	3/8"-24	7.56	192	1/4"	3/8"	10	283	2.76	1.25	10/Ctn/15kg/0.8'	3
AT-4131(S)	3/8	10	2300	3/8"-24	7.56	192	1/4"	3/8"	10	283	2.76	1.25	10/Ctn/15kg/0.8'	3
AT-4135(S)	3/8	10	2300	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4136(S)	3/8	10	2300	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4237	3/8	10	3000	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4237R	3/8	10	3000	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4330	3/8	10	2800	3/8"-24	7.87	200	1/4"	3/8"	12	340	2.20	1.00	10/Ctn/12kg/0.8'	3
AT-4331R	3/8	10	2000	3/8"-24	8.46	215	1/4"	3/8"	12	340	2.29	1.04	10/Ctn/12.5kg/0.8'	3
AT-4332	3/8	10	5600	3/8"-24	7.87	200	1/4"	3/8"	12	340	2.09	0.95	10/Ctn/11.5kg/0.8'	3
AT-4333	3/8	10	2600	3/8"-24	8.58	218	1/4"	3/8"	13	368	2.42	1.10	10/Ctn/13kg/0.8'	3
AT-4334R	3/8	10	2800	3/8"-24	9.21	234	1/4"	3/8"	13	283	2.42	1.10	10/Ctn/13kg/0.8'	3

S : with keyless chuck

1/4" & 3/8" AIR DRILL

AT-4023
2600 rpm 1/4" Composite air drill



AT-4022
2600 rpm 1/4" Composite reversible air drill



AT-4020
4500 rpm 1/4" Air drill



AT-4232
2000 rpm 3/8" composite air drill
AT-4232S
2000 rpm 3/8" composite air drill with keyless chuck



AT-4233
1800 rpm 3/8" composite reversible air drill
AT-4233S
1800 rpm 3/8" composite reversible air drill with keyless chuck



AT-4037
4500 rpm 3/8" Air drill
AT-4037S
4500 rpm 3/8" Air drill with keyless chuck



AT-4032
2300 rpm 3/8" reversible air drill



AT-4236
1650 rpm 3/8" reversible air drill



AT-4134
1500 rpm 3/8" Reversible air drill
AT-4134S
1500 rpm 3/8" Reversible air drill with keyless chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4020	1/4	6.5	4500	3/8"-24	6.22	158	1/4"	3/8"	8	226	1.50	0.68	20/Ctn/16 kg /1'	3
AT-4022	1/4	6.5	2600	3/8"-24	6.1	155	1/4"	3/8"	8	226	1.19	0.54	20/Ctn/15 kg /1'	3
AT-4023	1/4	6.5	2600	3/8"-24	6.1	155	1/4"	3/8"	8	226	1.19	0.54	20/Ctn/15 kg /1'	3
AT-4032	3/8	10	2600	3/8"-24	6.5	165	1/4"	3/8"	7	198	2.20	1.00	10/Ctn/12.9 kg /1'	3
AT-4037(S)	3/8	10	4500	3/8"-24	7.72	196	1/4"	3/8"	11	311	2.53	1.15	10/Ctn/13 kg /0.8'	3
AT-4134(S)	3/8	10	1500	3/8"-24	8.66	220	1/4"	3/8"	14	396	2.73	1.24	10/Ctn/15 kg /1'	3
AT-4232(S)	3/8	10	2000	3/8"-24	7.56	192	1/4"	3/8"	8.5	240	2.09	0.95	10/Ctn/11 kg /0.8'	3
AT-4233(S)	3/8	10	1800	3/8"-24	7.56	192	1/4"	3/8"	8.5	240	2.09	0.95	10/Ctn/11 kg /0.8'	3
AT-4236	3/8	10	1650	--	6.69	170	1/4"	3/8"	9	255	3.20	1.45	10/Ctn/18.5 kg /1.1'	3

S : with keyless chuck

3/8" AIR DRILL

AT-4030
1800 RPM 3/8" air drill
AT-4030S
1800 RPM 3/8" air drill
with keyless chuck



AT-4031
1800 RPM 3/8" air drill
AT-4031S
1800 RPM 3/8" reversible air drill
with keyless chuck



AT-4034
3/8" reversible air drill
AT-4034S
3/8" reversible air drill
with keyless chuck



AT-4234
3/8" Air drill
AT-4234S
3/8" Air drill with keyless chuck



AT-4235
3/8" reversible air drill
AT-4235S
3/8" reversible air drill
with keyless chuck



AT-4238
4500 rpm 3/8" straight air drill
AT-4238S
4500 rpm 3/8" straight air drill
with keyless chuck



AT-4038
3/8" straight air drill
AT-4038S
3/8" straight air drill
with keyless chuck



AT-4139
3/8" straight air drill
AT-4139S
3/8" straight air drill
with keyless chuck



AT-4035
3/8" angle air drill
AT-4035S
3/8" straight air drill
with keyless chuck



AT-4036
3/8" reversible angle air drill
AT-4036S
3/8" reversible angle air drill
with key less chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4030(S)	3/8	10	1800	3/8"-24	6.89	175	1/4"	3/8"	10	283	2.34	1.06	10/Ctn/13 kg /0.8'	3
AT-4031(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.36	1.07	10/Ctn/13 kg /0.8'	3
AT-4034(S)	3/8	10	1800	3/8"-24	7.48	190	1/4"	3/8"	13	368	2.51	1.14	10/Ctn/13.3 kg /1'	3
AT-4035(S)	3/8	10	1900	3/8"-24	7.68	195	1/4"	3/8"	9	255	2.36	1.07	10/Ctn/13kg/0.73'	3
AT-4036(S)	3/8	10	1700	3/8"-24	8.46	215	1/4"	3/8"	9	255	2.47	1.12	10/Ctn/16 kg /1.36'	3
AT-4038(S)	3/8	10	2600	3/8"-24	8.46	215	1/4"	3/8"	10.5	297	2.03	0.92	20/Ctn/20 kg /0.85'	3
AT-4139(S)	3/8	10	4500	3/8"-24	8.74	222	1/4"	3/8"	10	283	2.05	0.93	20/Ctn/22 kg /0.85'	3
AT-4234(S)	3/8	10	1800	3/8"-24	7.28	185	1/4"	3/8"	10	283	2.53	1.15	10/Ctn/13 kg /0.8'	3
AT-4235(S)	3/8	10	1800	3/8"-24	7.28	185	1/4"	3/8"	10	283	2.53	1.15	10/Ctn/13 kg /0.8'	3
AT-4238(S)	3/8	10	4500	3/8"-24	9.45	240	1/4"	3/8"	12	340	2.38	1.08	20/Ctn/23 kg /0.85'	3

S : with keyless chuck

1/2" & 5/8" AIR DRILL

AT-4340
700 rpm 1/2" air drill-0.6hp



AT-4341R
700 rpm 1/2" reversible air drill-0.6hp



AT-4342
500 rpm 1/2" air drill-0.6hp



AT-4049
1000 rpm 5/8" Reversible air drill



AT-4343
600 rpm 1/2" air drill-1hp



AT-4344R
500 rpm 1/2" reversible air drill-1hp



AT-4142
350 rpm 1/2" Air drill
AT-4145
500 rpm 1/2" Air drill
AT-4147
800 rpm 1/2" Air drill



AT-4142R
350 rpm 1/2" Reversible air drill
AT-4146
500 rpm 1/2" Reversible air drill
AT-4147R
800 rpm 1/2" Reversible air drill



AT-4144
600 rpm 1/2" Reversible air drill
AT-4144S
600 rpm 1/2" Reversible air drill with keyless chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4049	5/8	16	1000	-	16.14	410	3/8"	1/2"	19	538	13.7	6.22	4/Ctn/26 kg /1.5'	5
AT-4142(S)	1/2	13	350	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/0.98'	3
AT-4142R(S)	1/2	13	350	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/0.98'	3
AT-4144(S)	1/2	13	600	3/8"-24	9.84	250	1/4"	3/8"	14	396	3.59	1.63	10/Ctn/18 kg /1'	3
AT-4145(S)	1/2	13	500	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/0.98'	3
AT-4146(S)	1/2	13	500	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/0.98'	3
AT-4147(S)	1/2	13	800	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/0.98'	3
AT-4147R(S)	1/2	13	800	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/0.98'	3
AT-4340	1/2	13	700	1/2"-20	9.45	240	1/4"	3/8"	12	340	3.09	1.40	10/Ctn/16.5kg/0.98'	3
AT-4341R	1/2	13	700	1/2"-20	9.92	252	1/4"	3/8"	12	340	3.09	1.40	10/Ctn/16.5kg/0.98'	3
AT-4342	1/2	13	500	1/2"-20	9.45	240	1/4"	3/8"	12	340	3.09	1.40	10/Ctn/16.5kg/0.98'	3
AT-4343	1/2	13	600	1/2"-20	10.16	258	1/4"	3/8"	13	368	3.31	1.50	10/Ctn/17.5kg/1'	3
AT-4344R	1/2	13	500	1/2"-20	10.71	272	1/4"	3/8"	13	368	3.52	1.60	10/Ctn/18.5kg/1.1'	3

S : with keyless chuck

1/2" AIR DRILL

AT-4242
800 rpm 1/2" composite air drill
AT-4242S
800rpm 1/2" composite air drill .
with keyless chuck



AT-4140
500 rpm 1/2" Air drill
AT-4140S
500 rpm 1/2" Air drill with keyless chuck



AT-4040
800 rpm 1/2" air drill
AT-4040S
800 rpm 1/2" air drill with keyless chuck



AT-4243
800 rpm 1/2" composite reversible air drill
AT-4243S
800 rpm 1/2" composite reversible air drill
with keyless chuck



AT-4141
500 rpm 1/2" Reversible air drill
AT-4141S
500 rpm 1/2" Reversible air drill
with keyless chuck



AT-4041
800 rpm 1/2" reversible air drill
AT-4041S
800 rpm 1/2" reversible air drill
with keyless chuck



AT-4044
800 rpm 1/2" reversible air drill
AT-4044S
800 rpm 1/2" reversible air drill
with keyless chuck



AT-4244
800 rpm 1/2" air drill
AT-4244S
800 rpm 1/2" air drill with keyless chuck



AT-4245
800 rpm 1/2" Reversible air drill
AT-4245S
800 rpm 1/2" Reversible air drill
with keyless chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4040(S)	1/2	13	800	3/8"-24	8.74	222	1/4"	3/8"	10	283	3.26	1.48	10/Ctn/19kg/1'	3
AT-4041(S)	1/2	13	800	3/8"-24	8.98	228	1/4"	3/8"	12	340	3.37	1.53	10/Ctn/18.2kg/1.3'	3
AT-4044(S)	1/2	13	800	3/8"-24	8.94	227	1/4"	3/8"	12	340	3.46	1.57	10/Ctn/18.7kg/1'	3
AT-4140(S)	1/2	13	500	3/8"-24	8.86	225	1/4"	3/8"	10	283	3.96	1.80	10/Ctn/19kg/0.98'	3
AT-4141(S)	1/2	13	500	3/8"-24	8.86	225	1/4"	3/8"	10	283	3.96	1.80	10/Ctn/19kg/0.98'	3
AT-4242(S)	1/2	13	800	3/8"-24	9.65	245	1/4"	3/8"	8.5	240	3.09	1.40	10/Ctn/16kg/1'	3
AT-4243(S)	1/2	13	800	3/8"-24	9.65	245	1/4"	3/8"	8.5	240	3.09	1.40	10/Ctn/16kg/1'	3
AT-4244(S)	1/2	13	800	3/8"-24	8.27	210	1/4"	3/8"	10	283	3.09	1.40	10/Ctn/17kg/1'	3
AT-4245(S)	1/2	13	800	3/8"-24	8.27	210	1/4"	3/8"	10	283	3.17	1.44	10/Ctn/17.5kg/1'	3

S : with keyless chuck