

AIR SANDER



AT-7108C/S

Non-vacuum orbital air sander (Oil Free)



- * Oil-Free motor designed, use wearproof materials, the motor lifespan can promote more than 2 times.
- * 3 in 1 innovation design, easily switch to vacuum / non-vacuum / central vacuum modes.
- * Durable, lightweight and ergonomic composite design



AT-7108DC/DS

3 in 1 Orbital air sander (Oil Free)



AT-7102C/S

Non-vacuum orbital air sander



AT-7102DC/DS

3 in 1 Orbital air sander



AT-7004C/S

Non-vacuum orbital air sander



AT-7004DC/DS

Self-generated vacuum orbital air sander



AT-7004VC/VS

Central vacuum orbital air sander



* Working Air Pressure : 6.3 kg/cm² (90 psi)

* Air Inlet : 1/4" PT (NPT)

* Air Hose (I.D.) : 5/16" (8mm)

Model No.	Orbit Dia. mm	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight				Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm	scfm	l/min	5" Pad		6" Pad			
AT-7102CF/SF	2.5	10000	5/6	125/150	6.5	165	8.5	240	1.81	0.82	1.85	0.84	12/Ctn/13 kg/1.8'	3
AT-7102C/S	5	10000	5/6	125/150	6.5	165	8.5	240	1.85	0.84	1.92	0.87	12/Ctn/13 kg/1.8'	3
AT-7102CR/SR	9.5	10000	5/6	125/150	6.5	165	8.5	240	1.92	0.87	2.0	0.91	12/Ctn/13 kg/1.8'	3
AT-7102DCF/DSF	2.5	10000	5/6	125/150	7.28	185	8.5	240	1.81	0.82	1.9	0.86	12/Ctn/14.5 kg/1.8'	3
AT-7102DC/DS	5	10000	5/6	125/150	7.28	185	8.5	240	1.85	0.84	1.96	0.89	12/Ctn/14.5 kg/1.8'	3
AT-7102DCR/DSR	9.5	10000	5/6	125/150	7.28	185	8.5	240	1.92	0.87	2.05	0.93	12/Ctn/14.5 kg/1.8'	3
AT-7108CF/SF	2.5	10000	5/6	125/150	6.5	165	8.5	240	1.56	0.71	1.65	0.75	12/Ctn/13 kg/1.8'	3
AT-7108C/S	5	10000	5/6	125/150	6.5	165	8.5	240	1.61	0.73	1.72	0.78	12/Ctn/13 kg/1.8'	3
AT-7108CR/SR	9.5	10000	5/6	125/150	6.5	165	8.5	240	1.68	0.76	1.81	0.82	12/Ctn/13 kg/1.8'	3
AT-7108DCF/DSF	2.5	10000	5/6	125/150	7.28	185	8.5	240	1.54	0.7	1.7	0.77	12/Ctn/14.5 kg/1.8'	3
AT-7108DC/DS	5	10000	5/6	125/150	7.28	185	8.5	240	1.54	0.7	1.7	0.77	12/Ctn/14.5 kg/1.8'	3
AT-7108DCR/DSR	9.5	10000	5/6	125/150	7.28	185	8.5	240	1.72	0.78	1.85	0.84	12/Ctn/14.5 kg/1.8'	3
AT-7004C/S	5	10000	5/6	125/150	6.69	170	5.5	156	1.83	0.83	1.87	0.85	10/Ctn/18.5 kg/2.4'	3
AT-7004DC/DS	5	10000	5/6	125/150	9.84	250	5.5	156	1.94	0.88	1.98	0.90	10/Ctn/18.5 kg/3.1'	3
AT-7004VC/VS	5	10000	5/6	125/150	9.06	230	5.5	156	1.87	0.85	1.92	0.87	10/Ctn/18.5 kg/2.4'	3

D : with self-generated vacuum V : with central vacuum C : with velcro pad S : with stick pad
 F : orbit dia. : 2.5mm (for ultra fine sanding) R : orbit dia. : 9.5mm (for aggressive sanding)

AIR SANDER

AT-7203C/S
Non-vacuum orbital air sander



AT-7203DC/DS
Self-generated vacuum air sander



AT-7203VC/VS
Central vacuum orbital air sander



AT-7107C/S
Non-vacuum orbital air sander



AT-7107DC/DS
Self-generated vacuum orbital air sander



AT-7107VC/VS
Central vacuum orbital air sander



AT-7002C/S
Non-vacuum orbital air sander



AT-7002DC/DS
Self-generated vacuum orbital air sander



AT-7002VC/VS
Central vacuum orbital air sander



* Working Air Pressure : 6.3 kg/cm² (90 psi) * Air Inlet : 1/4" PT (NPT) * Air Hose (I.D.) : 5/16" (8mm)

Model No.	Orbit Dia. mm	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight				Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm	scfm	l/min	5" Pad		6" Pad			
AT-7002C/S	5	10000	5/6	125/150	6.61	168	7.5	212	2.20	1.00	2.25	1.02	10/Ctn/18.5 kg/2.4'	3
AT-7002DC/DS	5	10000	5/6	125/150	9.06	230	7.5	212	2.40	1.09	2.45	1.11	10/Ctn/18.5 kg/3.1'	3
AT-7002VC/VS	5	10000	5/6	125/150	8.27	210	7.5	212	2.36	1.07	2.4	1.09	10/Ctn/18.5 kg/2.4'	3
AT-7107C/S	5	10000	5/6	125/150	6.10	155	6.5	184	1.90	0.86	1.94	0.88	12/Ctn/17 kg/2.1'	3
AT-7107DC/DS	5	10000	5/6	125/150	9.45	240	6.5	184	2.12	0.96	2.16	0.98	6/Ctn/14.6 kg/2.2'	3
AT-7107VC/VS	5	10000	5/6	125/150	8.46	215	6.5	184	2.07	0.94	2.12	0.96	12/Ctn/17 kg/2.1'	3
AT-7203C/S	5	10000	5/6	125/150	5.59	142	7.5	212	1.70	0.77	1.74	0.79	10/Ctn/10 kg/1.8'	3
AT-7203DC/DS	5	10000	5/6	125/150	8.58	218	7.5	212	1.74	0.79	1.79	0.81	10/Ctn/12 kg/2.12'	3
AT-7203VC/VS	5	10000	5/6	125/150	8.58	218	7.5	212	1.74	0.79	1.79	0.81	10/Ctn/12 kg/2.12'	3

D : with self-generated vacuum V : with central vacuum C : with velcro pad S : with stick pad

AIR SANDER

AT-7205C/S
Non-vacuum orbital air sander



AT-7205DC/DS
Self-generated vacuum air sander



AT-7205VC/VS
Central vacuum orbital air sander



AT-7207C/S
Non-vacuum orbital air sander
AT-7207DC/DS
Self-generated vacuum air sander



AT-7043DC/DS
Self-generated vacuum orbital air sander



AT-7027
Non-vacuum orbital air sander
AT-7028
Self-generated vacuum air sander



AT-7023C/S
Self-generated vacuum orbital air sander



AT-7204C/S
Non-vacuum orbital air sander



AT-7015P
6" D/A air sander



* Working Air Pressure : 6.3 kg/cm² (90 psi) * Air Inlet : 1/4" PT (NPT) * Air Hose (I.D.) : 5/16" (8mm)

Model No.	Orbit Dia. mm	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight				Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm	scfm	l/min	5" Pad		6" Pad			
									lb	kg	lb	kg		
AT-7015P	5	10000	5/6	125/150	9.45	240	7	198	3.92	1.78	3.97	1.8	10/Ctn/22 kg/1.3'	3
AT-7023C/S	10	10000	5/6	125/150	11.89	302	9	255	4.01	1.82	4.06	1.84	6/Ctn/17.3 kg/2.3'	3
AT-7027	5	9000	5/6	125/150	6.10	155	6	170	2.38	1.08	2.42	1.1	12/Ctn/19.5 kg/1.9'	3
AT-7028	5	9000	5/6	125/150	6.10	155	6	170	2.47	1.12	2.51	1.14	12/Ctn/20.5 kg/1.9'	3
AT-7043DC/DS	5	10000	5/6	125/150	7.00	178	10.5	297	3.26	1.48	3.3	1.5	10/Ctn/20 kg/3.01'	3
AT-7204C/S	5	10000	5/6	125/150	5.51	140	8	226	1.45	0.66	1.5	0.68	10/Ctn/10.2 kg/1.7'	3
AT-7205C/S	5	10000	5/6	125/150	6.38	162	7	198	1.81	0.82	1.85	0.84	10/Ctn/18.5 kg/2.4'	3
AT-7205DC/DS	5	10000	5/6	125/150	9.57	243	7	198	2.03	0.92	2.07	0.94	10/Ctn/18.5 kg/3.1'	3
AT-7205VC/VS	5	10000	5/6	125/150	8.31	211	7	198	2.03	0.92	2.07	0.94	10/Ctn/18.5 kg/2.4'	3
AT-7207C/S	5	10000	5/6	125/150	9.84	250	9	255	2.34	1.06	2.38	1.08	6/Ctn/10.0 kg/1.9'	3
AT-7207DC/DS	5	10000	5/6	125/150	9.84	250	9	255	2.34	1.06	2.38	1.08	6/Ctn/10.0 kg/1.9'	3

D : with self-generated vacuum V : with central vacuum C : with velcro pad S : with stick pad

AIR SANDER

AT-7106
Non-vacuum orbital air sander (Clip type)
AT-7106DC
Self-generated vacuum orbital air sander
AT-7106VC
Central vacuum orbital air sander



AT-7025DC/DS
Air jitterbug sander



AT-7206C
Non-vacuum orbital air sander (Clip type)
AT-7206DC
Self-generated vacuum orbital air sander



AT-7029
Non-vacuum jitterbug sander
AT-7030
Self-generated vacuum jitterbug sander



AT-7104F
Non-vacuum jitterbug sander (Clip type)
AT-7104C
Non-vacuum jitterbug sander



AT-7105C
Non-vacuum triangle sander



AT-7018
Air jitterbug sander



AT-7017
Air palm sander



AT-7017S
Air palm sander



AT-7019
Twin-piston straight line sander



* Working Air Pressure : 6.3 kg/cm² (90 psi) * Air Inlet : 1/4" PT (NPT) * Air Hose (I.D.) : 5/16" (8mm)

Model No.	Orbit Dia. mm	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm	scfm	l/min	lb	kg		
AT-7017	1.60	20000	4x4.33	100x110	5.51	140	4	113	1.06	0.48	20/Ctn/18 kg/2.3'	2
AT-7017S	1.20	15000	3x3.23	75x82	6.10	155	3	85	0.93	0.42	20/Ctn/17 kg/2.3'	2
AT-7018	5.00	8000	3.7x7	93x176	7.28	185	7	198	4.19	1.90	10/Ctn/23 kg/1.3'	3
AT-7019	25.40	2500	2.5x16	63.5x400	15.75	400	6	170	6.13	2.78	6/Ctn/18.7 kg/1.4'	3
AT-7025	5.00	7000	3.7x7	93x176	8.66	220	8	226	4.23	1.92	10/Ctn/23 kg/1.44'	3
AT-7029	5.00	8000	3x6	75x145	6.30	160	6	170	2.69	1.22	12/Ctn/19.5 kg/1.9'	3
AT-7030	5.00	8000	3x6	75x145	6.69	170	6	170	2.73	1.24	12/Ctn/20.5 kg/1.9'	3
AT-7104F	2.50	10000	4x4.33	100x110	5.16	131	7	198	2.00	0.91	12/Ctn/13.9 kg/1.8'	3
AT-7104C	5.00	10000	4x4.33	100x110	5.16	131	7	198	1.79	0.81	12/Ctn/13.9 kg/1.8'	3
AT-7105C	5.00	10000	5x3.74	125x95	6.26	159	7	198	1.79	0.81	12/Ctn/13.9 kg/1.8'	3
AT-7106	2.50	9000	3.7x7	93x176	7.09	180	6	170	2.45	1.11	10/Ctn/18.5 kg/2.4'	3
AT-7106DC	2.50	9000	3.7x7	93x176	10.08	256	6	170	2.42	1.10	10/Ctn/18.5 kg/3.1'	3
AT-7106VC	2.50	9000	3.7x7	93x176	8.78	223	6	170	2.40	1.09	10/Ctn/18.5 kg/2.4'	3
AT-7206C	5.00	9000	3.7x7	93x176	11.34	288	9.5	269	2.82	1.28	6/Ctn/10 kg/1.9'	3
AT-7206DC	5.00	9000	3.7x7	93x176	11.34	288	9.5	269	2.82	1.28	6/Ctn/10 kg/1.9'	3

D : with self-generated vacuum V : with central vacuum C : with velcro pad S : with stick pad

MIN AIR SANDER

AT-7215A
3" Composite orbital air Sander
AT-7215B
2" Composite orbital air Sander



AT-7315B
2" orbital air Sander
AT-7315C
1-1/4" orbital air Sander
AT-7315D
1" orbital air Sander



AT-7218A
3" Orbital air Sander



AT-7116A
3" micro orbital sander
AT-7116B
2" micro orbital sander



AT-7316C
1-1/4" orbital air Sander



AT-7118A
3" Orbital air sander
AT-7118B
2" Orbital air sander



AT-7117
3" micro sander



AT-7214
3" Surface Preparation Tool



AT-7119
3" angle sander



* Working Air Pressure : 6.3 kg/cm² (90 psi) * Air Inlet : 1/4" PT (NPT) * Air Hose (I.D.) : 5/16" (8mm)

Model No.	Orbit Dia. mm	Spindle Thread	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
				inch	mm	inch	mm	scfm	l/min	lb	kg		
AT-7116A	3	M6×P1.0	15000	3	75	4.05	103	9	255	1.63	0.74	20/Ctn/15 kg/1.28'	3
AT-7116B	3	M6×P1.0	15000	2	50	4.05	103	9	255	1.63	0.74	20/Ctn/15 kg/1.28'	3
AT-7118A	3	5/16"-24UNF	16000	3	75	6.3	160	8	226	1.65	0.75	20/Ctn/18 kg/1.0'	3
AT-7118B	3	5/16"-24UNF	16000	2	50	6.3	160	8	226	1.65	0.75	20/Ctn/18 kg/1.0'	3
AT-7215A	3	5/16"-24UNF	15000	3	75	5.98	152	8.5	240	1.76	0.8	10/Ctn/9 kg/1.0'	3
AT-7215B	3	5/16"-24UNF	15000	2	50	5.98	152	8.5	240	1.76	0.8	10/Ctn/9 kg/1.0'	3
AT-7218A	3	5/16"-24UNF	16000	3	75	9.84	250	10	283	2.4	1.09	20/Ctn/22 kg/1.6'	3
AT-7315B	2.5	M6×P1.0	10000	2	50	4.72	120	8	226	1.15	0.52	20/Ctn/11 kg/1.0'	3
AT-7315C	2.5	M6×P1.0	10000	1-1/4	30	4.72	120	8	226	1.15	0.52	20/Ctn/11 kg/1.0'	3
AT-7315D	2.5	M6×P1.0	10000	1	25	4.72	120	8	226	1.15	0.52	20/Ctn/11 kg/1.0'	3
AT-7316C	2.5	M6×P1.0	8000	1-1/4	30	6.3	160	8	226	1.21	0.55	20/Ctn/11 kg/1.0'	3

Model No.	Spindle Thread	Free Speed RPM	Sanding Pad Size		Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm	scfm	l/min	lb	kg		
AT-7117	1/4"-20UNC	15000	3	75	4.72	120	8	226	1.45	0.66	20/Ctn/13.5 kg/1.28'	3
AT-7119	1/4"-20UNC	18000	3	75	6.30	160	8	226	1.23	0.56	20/Ctn/18 kg/1.0'	3
AT-7214	1/4"-20UNC	15000	3	75	5.28	134	8.5	240	1.54	0.70	10/Ctn/8 kg/1'	3

HIGH SPEED SANDER & POLISHER

AT-7213
5" high speed air sander
(rear exhaust)



AT-7112
5" high speed air sander
(front exhaust)



AT-7113
5" high speed air sander
(rear exhaust)



AT-7012
5" high speed air sander
(front exhaust)



AT-7170
5" vertical air polisher



AT-7172
7" vertical air polisher



AT-7070
7" vertical air polisher
AT-7070S
7" vertical air sander



AT-7078
7" vertical air sander
AT-7079
7" vertical air polisher



AT-7173
7" air angle polisher



AT-7071
3" Air Composite Polisher



AT-7171
3" micro polisher



AT-7072
3" Air Polisher



Model No.	Sanding Pad Size		Spindle Thread	Free Speed RPM	Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm	scfm	l/min	lb	kg		
AT-7012	5	125	7/16"-20NF	18000	4.92	125	8	226	2.07	0.94	10/Ctn/12.2 kg/0.95'	3
AT-7112	5	125	7/16"-20NF	16000	5.91	150	8	226	2.16	0.98	10/Ctn/12 kg/0.8'	3
AT-7113	5	125	7/16"-20NF	18000	5.91	150	8	226	2.20	1.00	10/Ctn/12 kg/0.8'	3
AT-7213	5	125	7/16"-20NF	18000	5.71	145	8.5	241	2.87	1.30	10/Ctn/14 kg/1'	3
AT-7070	7	178	5/8"-11 UNC	2000	7.09	180	14	396	4.10	1.86	8/Ctn/21.3 kg/1.34'	5
AT-7070S	7	178	5/8"-11 UNC	4000	7.09	180	14	396	4.10	1.86	8/Ctn/21.6 kg/1.34'	5
AT-7071	3	75	5/16"-24	2100	6.34	161	8.5	240	1.70	0.77	10/Ctn/9 kg/1'	3
AT-7072	3	75	5/16"-24	3200	8.66	220	8	226	2.38	1.08	10/Ctn/12/1.7'	3
AT-7078	7	178	5/8"-11 UNC	4500	13.0	330	8	226	4.01	1.82	10/Ctn/23 kg/1.6'	3
AT-7079	7	178	5/8"-11 UNC	2500	13.0	330	8	226	4.01	1.82	10/Ctn/23 kg/1.6'	3
AT-7170	5	125	5/8"-11 / 5/16"-24	3000	8.07	205	8	226	2.47	1.12	10/Ctn/13.5 kg/1.7'	3
AT-7171	3	75	M6xP1.0	2500	4.45	113	9	255	1.86	0.82	20/Ctn/18 kg/1.28'	3
AT-7172	7	178	5/8"-11 UNC	4000	10.63	270	15	425	4.08	1.85	6/Ctn/14 kg/2'	5
AT-7173	7	178	5/8"-11 UNC	2800	11.50	290	14	396	3.26	1.48	10/Ctn/16 kg/1.8'	5

AIR BELT SANDER

AT-7220
Air belt sander (6x457mm)



AT-7221
Air belt sander (10x330mm)



AT-7222
Air belt sander w/steel pulley (20x520mm)
AT-7222P
Air belt sander w/pu pulley (20x520mm)



AT-7223
Air belt sander w/steel pulley (30x540mm)
AT-7223P
Air belt sander w/pu pulley (30x540mm)



AT-7224
Air belt sander (30x640mm)



AT-7109
Air belt sander (30x540mm)



AT-7122
Air belt sander (50x235mm)



AT-7110
Air belt sander (60x260mm)



Model No.	Sanding Belt Size		Free Speed RPM	Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm		inch	mm	scfm	l/min	lb	kg		
AT-7109	1-3/16x21-1/4	30x540	12000	14.96	380	13	368	4.41	2.00	6/Ctn/15 kg/2.5'	3
AT-7110	2-3/8x10-1/4	60x260	6000	7.28	185	8	226	3.09	1.40	10/Ctn/15 kg/2.0'	3
AT-7122	2x9-1/4	50x235	8500	8.80	223	8	226	1.68	0.76	10/Ctn/9 kg/1.0'	3
AT-7220	1/4x18	6x457	17000	15.35	390	8	226	2.20	1.00	10/Ctn/12 kg/2.0'	3
AT-7221	25/64x13	10x330	17000	12.83	326	8	226	1.94	0.88	20/Ctn/18.6 kg/1.4'	3
AT-7222	25/32x20	20x520	16000	16.02	407	8	226	2.87	1.30	10/Ctn/14 kg/2.0'	3
AT-7222P	25/32x20	20x520	16000	16.02	407	8	226	2.87	1.30	10/Ctn/14 kg/2.0'	3
AT-7223	1-3/16x21-1/4	30x540	13000	16.38	416	14	396	3.09	1.40	10/Ctn/16 kg/2.0'	5
AT-7223P	1-3/16x21-1/4	30x540	13000	16.38	416	14	396	3.09	1.40	10/Ctn/16 kg/2.0'	5
AT-7224	1-3/16x25-3/16	30x640	13000	15.35	390	14	396	4.23	1.92	6/Ctn/13 kg/2.0'	5

AIR BELT SANDER

AT-7126
Air belt sander (20×520mm)



AT-7129
Air belt sander (20×520mm)



AT-7124
Air belt sander (6×330mm)



AT-7125
Air belt sander (10×330mm)



AT-7127
Air belt sander (12.7×610mm)



AT-7009
Air belt sander (10×330mm)



AT-7010
Air belt sander (20×520mm)



AT-7111
Air belt sander (12.7×610mm)



Model No.	Sanding Belt Size		Free Speed RPM	Overall Length		Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm		inch	mm	scfm	l/min	lb	kg		
AT-7009	25/64×13	10×330	16000	11.42	290	8	226	1.94	0.88	20/Ctn/17 kg/1.4'	3
AT-7010	25/32×20	20×520	16000	14.17	360	8	226	2.56	1.16	10/Ctn/13 kg/1.8'	3
AT-7111	1/2×24	12.7×610	16000	16.93	430	8	226	2.29	1.04	10/Ctn/10.6 kg/1.1'	3
AT-7124	1/4×13	6×330	16000	12.6	320	8	226	2.09	0.95	10/Ctn/11 kg/1.4'	3
AT-7125	25/64×13	10×330	16000	12.6	320	8	226	2.09	0.95	10/Ctn/11 kg/1.4'	3
AT-7126	25/32×20	20×520	16000	16.93	430	8	226	3.09	1.4	10/Ctn/15 kg/1.4'	3
AT-7127	1/2×24	12.7×610	16000	17.91	455	8	226	2.42	1.1	10/Ctn/13 kg/1.4'	3
AT-7129	25/32×20	20×520	16000	15.35	390	8	226	3.02	1.37	10/Ctn/15 kg/1.4'	3