

# AIR HAMMER

**AT-2023Q/H**  
190mm air hammer W/Built In Chuck (hex.)  
**AT-2023Q/R**  
190mm air hammer W/Built In Chuck (round)



**AT-2024Q/H**  
250mm air hammer W/Built In Chuck (hex.)  
**AT-2024Q/R**  
250mm air hammer W/Built In Chuck (round)



**AT-2025/H**  
250mm air hammer (hex.)  
**AT-2025/R**  
250mm air hammer (round)



**AT-2038/H**  
Vibration-damped 190mm air hammer (hex)  
**AT-2038/R**  
Vibration-damped 190mm air hammer (round)



**AT-2039/H**  
Vibration-damped 250mm air hammer (hex)  
**AT-2039/R**  
Vibration-damped 250mm air hammer (round)



**AT-2038K**  
Vibration-damped 190mm air hammer kit  
**AT-2039K**  
Vibration-damped 250mm air hammer kit



**AT-2014/H**  
135mm air hammer(hex.)  
**AT-2014/R**  
135mm air hammer(round)



**AT-2017/H**  
190mm air hammer(hex.)  
**AT-2017/R**  
190mm air hammer(round)



**AT-2018/H**  
250mm air hammer(hex.)  
**AT-2018/R**  
250mm air hammer(round)



Model No.	Chisel Shank (inch)		Bore Diameter (I.D)		Piston Stroke Length		Blow per min. (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Round	Hex.	inch	mm	inch	mm		inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
<b>AT-2014</b>	0.401	0.410	45/64	17.08	2.00	51	4500	6.10	155	1/4"	3/8"	10	283	3.09	1.40	90	6.3	10/Ctn/16 kg/0.65'	2
<b>AT-2017</b>	0.401	0.410	3/4	19.05	2.72	69	3000	7.00	260	1/4"	3/8"	10	283	3.74	1.70	90	6.3	10/Ctn/19 kg/0.8'	2
<b>AT-2018</b>	0.401	0.410	3/4	19.05	3.78	96	2100	10.00	255	1/4"	3/8"	10	283	5.29	2.40	90	6.3	10/Ctn/26 kg/1.0'	2
<b>AT-2023Q</b>	0.401	0.410	3/4	19.05	2.80	71	3000	9.65	245	1/4"	3/8"	8.5	241	4.41	2.00	90	6.3	10/Ctn/21 kg/1.0'	2
<b>AT-2024Q</b>	0.401	0.410	3/4	19.05	3.62	92	2200	10.39	264	1/4"	3/8"	8.5	241	5.29	2.40	90	6.3	8/Ctn/20 kg/1.3'	2
<b>AT-2025</b>	0.401	0.410	3/4	19.05	3.62	92	2100	9.45	240	1/4"	3/8"	10	283	4.96	2.25	90	6.3	10/Ctn/24.5 kg/1.6'	2
<b>AT-2038</b>	0.401	0.410	3/4	19.05	2.80	71	3000	8.46	215	1/4"	3/8"	8.5	241	3.53	1.60	90	6.3	10/Ctn/19 kg/1.6'	2
<b>AT-2039</b>	0.401	0.410	3/4	19.05	3.62	92	2100	10.24	260	1/4"	3/8"	8.5	241	4.19	1.90	90	6.3	10/Ctn/22.5 kg/1.6'	2

Model No.	AT-2038K/H	AT-2038K/R	AT-2039K/H	AT-2039K/R
<b>Contents</b>	1 Pc Air Hammer, AT-2038/H 1 Pc Retainer Spring 1 Pc Quick Change Retainer 5 Pcs 7" Chisels 1 Pc Blow Case 1 Pc Nipple Net Weight : 3.5 kg Packing : 5 Set/Ctn/19 kg/1.7'	1 Pc Air Hammer, AT-2038/R 1 Pc Retainer Spring 1 Pc Quick Change Retainer 5 Pcs 7" Chisels 1 Pc Blow Case 1 Pc Nipple Net Weight : 3.5 kg Packing : 5 Set/Ctn/19 kg/1.7'	1 Pc Air Hammer, AT-2039/H 1 Pc Retainer Spring 1 Pc Quick Change Retainer 5 Pcs 7" Chisels 1 Pc Blow Case 1 Pc Nipple Net Weight : 3.8 kg Packing : 5 Set/Ctn/21 kg/1.7'	1 Pc Air Hammer, AT-2039/R 1 Pc Retainer Spring 1 Pc Quick Change Retainer 5 Pcs 7" Chisels 1 Pc Blow Case 1 Pc Nipple Net Weight : 3.8 kg Packing : 5 Set/Ctn/21 kg/1.7'

**R** : for round chisel shank **H** : for hex. chisel shank

# AIR HAMMER

**AT-2015/H** 190mm air hammer (hex)  
**AT-2015/R** 190mm air hammer (round)



**AT-2016/H** 250mm air hammer (hex)  
**AT-2016/R** 250mm air hammer (round)



**AT-2036H** 190mm air hammer w/quick change retainer  
**AT-2036/R** 190mm air hammer w/quick change retainer (round)



**AT-2037H** 250mm air hammer w/quick change retainer  
**AT-2037/R** 250mm air hammer w/quick change retainer (round)



**AT-2011/H** 150mm 50air hammer (hex)  
**AT-2011/R** 150mm air hammer (round)



**AT-2012/H** 190mm air hammer (hex)  
**AT-2012/R** 190mm air hammer (round)



**AT-2013/H** 250mm air hammer (hex)  
**AT-2013/R** 250mm air hammer (round)



**AT-2012K/H** 9 pcs air hammer (hex)  
**AT-2012K/R** 9 pcs air hammer (round)



**AT-2010/H** 150mm air hammer w/4 pcs chisel (hex)  
**AT-2010/R** 150mm air hammer w/4 pcs chisel (round)



**AT-2020/H** 190mm air hammer w/4 pcs chisel (hex)  
**AT-2020/R** 190mm air hammer w/4 pcs chisel (round)



**AT-2030/H** 250mm air hammer w/4 pcs chisel (hex)  
**AT-2030/R** 250mm air hammer w/4 pcs chisel (round)



**AT-2020K/H** Air hammer & attachment kit (hex)  
**AT-2020K/R** Air hammer & attachment kit (round)



Model No.	Chisel Shank (inch)		Bore Diameter (I.D)		Piston Stroke Length		Blow per min. (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Round	Hex.	inch	mm	inch	mm		inch	mm			scfm	l/min	lb	kg		
<b>AT-2010</b>	0.401	0.410	3/4	19.05	1-5/8	41	4500	5.24	133	1/4"	3/8"	10	283	3.09	1.40	10/Ctn/17.6 kg/0.88'	2
<b>AT-2011</b>	0.401	0.410	3/4	19.05	1-5/8	41	4500	5.24	133	1/4"	3/8"	10	283	3.09	1.40	10/Ctn/14.2 kg/0.88'	2
<b>AT-2012</b>	0.401	0.410	3/4	19.05	2-5/8	66	3000	7.00	178	1/4"	3/8"	10	283	3.53	1.60	10/Ctn/17.6 kg/0.9'	2
<b>AT-2013</b>	0.401	0.410	3/4	19.05	3-5/8	92	2200	8.50	216	1/4"	3/8"	10	283	4.50	2.04	10/Ctn/20 kg/1.2'	2
<b>AT-2015</b>	0.401	0.410	3/4	19.05	2-5/8	66	3000	7.00	178	1/4"	3/8"	10	283	3.53	1.60	10/Ctn/18 kg/0.9'	2
<b>AT-2016</b>	0.401	0.410	3/4	19.05	3-5/8	92	2200	10.00	255	1/4"	3/8"	10	283	5.29	2.40	10/Ctn/21 kg/1.2'	2
<b>AT-2020</b>	0.401	0.410	3/4	19.05	2-5/8	66	3000	7.00	178	1/4"	3/8"	10	283	3.53	1.60	10/Ctn/21 kg/0.9'	2
<b>AT-2030</b>	0.401	0.410	3/4	19.05	3-5/8	92	2200	8.50	216	1/4"	3/8"	10	283	4.50	2.04	10/Ctn/25.4 kg/1.2'	2
<b>AT-2036</b>	0.401	0.401	3/4	19.05	2-5/8	66	3200	6.93	176	1/4"	3/8"	7	198	3.70	1.68	5/Ctn/12.2 kg/0.5'	2
<b>AT-2037</b>	0.401	0.401	3/4	19.05	3-3/4	97	2200	8.86	225	1/4"	3/8"	7	198	4.45	2.02	5/Ctn/14 kg/0.63'	2

**R** : for round chisel shank **H** : for hex. chisel shank

# RIVETING HAMMER

**AT-2213**  
Vibration-damped Air riveting hammer



**AT-2211**  
Vibration-damped Air riveting hammer



**AT-2212**  
Vibration-damped Air riveting hammer



**AT-2201**  
Air riveting hammer



**AT-2202**  
Air riveting hammer



**AT-2203**  
Air riveting hammer



**AT-2204**  
Air riveting hammer



**AT-2205**  
Air riveting hammer



**AT-2207**  
Air riveting hammer



**AT-2209**  
Air riveting hammer



Model No.	Chisel Shank		Piston Diameter		Piston Stroke		Blow per min. (B.P.M.)	Riveting capacity	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Work Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp (HP)
	inch	mm	inch	mm	inch	mm			inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
AT-2201	0.401	10.2	0.56	14.30	1.97	50.0	2850	2.4	4.49	115	1/4"	3/8"	10	283	2.51	1.14	90	6.3	10/Ctn/15.5 kg/1.16'	3
AT-2202	0.401	10.2	0.50	12.70	2.25	57.2	2580	2.4	6.7	170	1/4"	3/8"	10	283	2.78	1.26	90	6.3	10/Ctn/15.5 kg/1.16'	3
AT-2203	0.401	10.2	0.50	12.70	2.87	73.0	2160	4	7.3	186	1/4"	3/8"	10	283	3.00	1.36	90	6.3	10/Ctn/16.5 kg/1.16'	3
AT-2204	0.401	10.2	0.50	12.70	3.06	77.8	1740	4.8	8.3	211	1/4"	3/8"	10	283	3.31	1.50	90	6.3	10/Ctn/17.5 kg/1.16'	3
AT-2205	0.498	12.6	0.75	19.10	2.69	68.3	1600	4.8	9.1	230	1/4"	3/8"	10	283	4.74	2.15	90	6.3	10/Ctn/26 kg/1.6'	3
AT-2207	0.498	12.6	0.75	19.10	3.87	98.4	1140	6.4	10.1	256	1/4"	1/4"	10	283	5.11	2.32	90	6.3	10/Ctn/28 kg/1.6'	3
AT-2209	0.498	12.6	0.75	19.10	5.81	147.6	900	8	11.2	284	1/4"	3/8"	10	283	5.99	2.72	90	6.3	10/Ctn/30.5 kg/1.6'	3
AT-2211	0.401	10.2	0.60	15.24	4.00	102.0	2160	3~6	8.9	225	1/4"	3/8"	9	255	2.93	1.33	90	6.3	10/Ctn/16.5 kg/1.4'	3
AT-2212	0.401	10.2	0.60	15.24	5.39	137.0	1440	4~7	10.4	260	1/4"	3/8"	9	255	3.22	1.46	90	6.3	10/Ctn/17.8 kg/1.4'	3
AT-2213	0.401	10.2	0.60	15.24	1.00	25.0	3960	1~4	6.5	165	1/4"	3/8"	9	255	2.40	1.09	90	6.3	10/Ctn/14.5 kg/0.82'	3

# RIVETING HAMMER

**AT-2210**  
Air riveting hammer



**AT-2290**  
One shot hammer



**AT-2291**  
One shot hammer



**AT-2214**  
Air riveting hammer



**AT-2215**  
Air riveting hammer



**AT-2216**  
Air riveting hammer



**AT-2217**  
Air riveting hammer



Model No.	Chisel Shank		Piston Diameter		Piston Stroke		Blow per min. (B.P.M.)	Riveting capacity	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Work Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm	inch	mm			inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
AT-2210	0.315	8.0	0.39	10.0	1.22	31.0	5400	1.5	5.90	165	1/4"	1/4"	3	85	0.88	0.40	90	6.3	12/Ctn/5.3 kg/0.3'	1.5
AT-2214	0.401	10.2	0.56	14.3	1.97	50.0	2850	2.0	6.30	160	1/4"	3/8"	10	283	2.03	0.92	90	6.3	10/Ctn/14.5 kg/1.16'	3
AT-2215	0.401	10.2	0.50	12.7	2.25	57.2	2580	2.4	8.46	215	1/4"	3/8"	10	283	2.34	1.06	90	6.3	10/Ctn/15.5 kg/1.16'	3
AT-2216	0.401	10.2	0.50	12.7	2.87	73.0	2160	4.0	9.09	231	1/4"	3/8"	10	283	2.56	1.16	90	6.3	10/Ctn/16.5 kg/1.16'	3
AT-2217	0.401	10.2	0.50	12.7	3.06	77.8	1740	4.8	10.08	256	1/4"	3/8"	10	283	2.80	1.27	90	6.3	10/Ctn/17.5 kg/1.16'	3
AT-2290	HEX. 7.9mm	1.18	30.0	1.00	25.0	-	-	-	10.00	254	1/4"	1/4"	0.65L/stroke	2.86	1.30	90	6.3	10/Ctn/14.5 kg/0.82'	1	
AT-2291	HEX. 7.9mm	1.18	30.0	1.00	25.0	-	-	-	8.39	213	1/4"	1/4"	0.25L/stroke	1.98	0.90	90	6.3	10/Ctn/10.5 kg/0.82'	1	

# AIR CHIPPING HAMMER

 **AT-2104/H**  
4" chipping hammer (hex.)  
**AT-2104/R**  
4" chipping hammer (round)



 **AT-2103/H**  
3" chipping hammer (hex.)  
**AT-2103/R**  
3" chipping hammer (round)



 **AT-2102/H**  
2" chipping hammer (hex.)  
**AT-2102/R**  
2" chipping hammer (round)



 **AT-2101/H**  
1" chipping hammer (hex.)  
**AT-2101/R**  
1" chipping hammer (round)



 **AT-2100/H**  
Mini chipping hammer (hex.)  
**AT-2100/R**  
Mini chipping hammer (round)



 **AT-2110/H**  
Mini chipping hammer (hex.)  
**AT-2110/R**  
Mini chipping hammer (round)



Model No.	Chisel Shank (mm)		Piston Diameter		Piston Stroke		Blow per min. (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Work Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Hex.	Round	inch	mm	inch	mm		inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
<b>AT-2100H/R</b>	12	14	25/32	20.0	1.77	45.0	3000	12.4	310	1/4"	3/8"	12	360	5.7	2.6	90	6.3	10/Ctn/31.5 kg/1.45'	3
<b>AT-2110H/R</b>	12	14	25/32	20.0	1.77	45.0	3000	12.4	310	1/4"	3/8"	12	360	5.7	2.6	90	6.3	10/Ctn/31.5 kg/1.45'	3
<b>AT-2101H/R</b>	14.7	17.3	1 1/8	28.5	1.00	25.4	2820	15.2	385	3/8"	1/2"	16	453	12.0	5.5	90	6.3	2/Ctn/15.7 kg/0.87'	5
<b>AT-2102H/R</b>	14.7	17.3	1 1/8	28.5	2.00	51.0	2150	16.1	410	3/8"	1/2"	18	515	13.0	5.9	90	6.3	2/Ctn/15.9 kg/1.0'	5
<b>AT-2103H/R</b>	14.7	17.3	1 1/8	28.5	3.00	76.0	1920	16.9	430	3/8"	1/2"	20	566	14.3	6.5	90	6.3	2/Ctn/16.9 kg/1.06'	5
<b>AT-2104H/R</b>	14.7	17.3	1 1/8	28.5	4.00	102.0	1500	18.1	460	3/8"	1/2"	22	629	15.5	7.0	90	6.3	2/Ctn/17 kg/1.08'	5

R : for round chisel shank H : for hex. chisel shank

# AIR CHIPPING HAMMER & CONCRETE BREAKER

**AT-2109/H**  
4" chipping hammer (hex.)  
**AT-2109/R**  
4" chipping hammer (round)



**AT-2108/H**  
3" chipping hammer (hex.)  
**AT-2108/R**  
3" chipping hammer (round)



**AT-2107/H**  
2" chipping hammer (hex.)  
**AT-2107/R**  
2" chipping hammer (round)



**AT-2115**  
Concrete Breaker



**AT-2116**  
Concrete Breaker



Model No.	Chisel Shank (mm)		Piston Diameter		Piston Stroke		Blow per min. (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Work Air Pressure		Packing Pcs/Ctn/G W/Cuft (kg)	Sug. Air Comp. (HP)
	Hex.	Round	inch	mm	inch	mm		inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
<b>AT-2107H/R</b>	14.7	17.3	1 1/8	28.5	2.00	51	2200	14.4	365	3/8"	1/2"	18	515	17.7	8.04	90	6.3	2/Ctn/17.6 kg/0.95'	5
<b>AT-2108H/R</b>	14.7	17.3	1 1/8	28.5	3.00	76	1900	15.8	400	3/8"	1/2"	20	566	18.7	8.50	90	6.3	2/Ctn/18.5 kg/1.01'	5
<b>AT-2109H/R</b>	14.7	17.3	1 1/8	28.5	4.00	102	1500	16.7	425	3/8"	1/2"	22	629	19.6	8.88	90	6.3	2/Ctn/19.6 kg/1.07'	5
<b>AT-2115</b>	30mm		1.57"	40.0	9.25	235	1000	23.2	590	-	3/4"	35	990	54.2	24.60	90	6.3	1/Ctn/26.5 kg/0.9'	10
<b>AT-2116</b>	26mm		1.38"	35.0	5.94	151	1300	17.2	438	-	1/2"	28	792	31.1	14.10	90	6.3	1/Ctn/15.6 kg/0.7'	7.5

**R** : for round chisel shank **H** : for hex. chisel shank