

AIR RATCHET WRENCH

AT-53584
1/2" Air ratchet wrench
AT-53583
3/8" Air ratchet wrench



AT-54524
1/2" Air ratchet wrench
AT-54523
3/8" Air ratchet wrench



AT-54544
1/2" Air impact ratchet wrench
AT-54543
3/8" Air impact ratchet wrench



AT-53574
1/2" Air ratchet wrench
AT-53573
3/8" Air ratchet wrench



AT-5057
1/2" Air ratchet wrench
AT-5056
3/8" Air ratchet wrench



AT-5053
1/2" Air ratchet wrench
AT-5052
3/8" Air ratchet wrench



AT-5001
17 pcs 3/8" Air ratchet wrench kit
AT-5002
17 pcs 1/2" Air ratchet wrench kit
AT-5056K
17 pcs 3/8" Air ratchet wrench kit
AT-5057K
17 pcs 1/2" Air ratchet wrench kit



Model No.	AT-5001	AT-5002
Contents	1 Pc AT-5052 air ratchet wrench 7 Pcs impact socket : 10,11,12,13,14,17,19 mm 1 Pc 3"L extension bar 1 Pc 3"L bit extension bar 1 Pc U-joint 1 Pc oil pot 3 Pcs bit 1 Pc male coupler 1 Pc blow case Packing : 5 Set/Ctn/13 kg/0.84'	1 Pc AT-5053 air ratchet wrench 7 Pcs impact socket : 10,11,12,13,14,17,19 mm 1 Pc 3"L extension bar 1 Pc 3"L bit extension bar 1 Pc U-joint 1 Pc oil pot 3 Pcs bit 1 Pc male coupler 1 Pc blow case Packing : 5 Set/Ctn/13 kg/0.84'
Model No.	AT-5056K	AT-5057K
Contents	1 Pc AT-5056 air ratchet wrench 7 Pcs impact socket : 10,11,12,13,14,17,19 mm 1 Pc 3"L extension bar 1 Pc 3"L bit extension bar 1 Pc U-joint 1 Pc oil pot 3 Pcs bit 1 Pc male coupler 1 Pc blow case Packing : 5 Set/Ctn/13 kg/0.84'	1 Pc AT-5057 air ratchet wrench 7 Pcs impact socket : 10,11,12,13,14,17,19 mm 1 Pc 3"L extension bar 1 Pc 3"L bit extension bar 1 Pc U-joint 1 Pc oil pot 3 Pcs bit 1 Pc male coupler 1 Pc blow case Packing : 5 Set/Ctn/13 kg/0.84'

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5052	3/8"	3/8	10	160	50	68	10.4	265	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/26.0 kg /1.2'	2
AT-5053	1/2"	3/8	10	160	50	68	10.4	265	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/26.0 kg /1.2'	2
AT-5056	3/8"	3/8	10	160	60	81	10.4	265	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/26.0 kg /1.2'	2
AT-5057	1/2"	3/8	10	160	60	81	10.4	265	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/26.0 kg /1.2'	2
AT-53573	3/8"	1/2	10	160	60	81	10.6	270	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/25 kg /1.2'	2
AT-53574	1/2"	1/2	10	160	60	81	10.6	270	1/4"	3/8"	8	226	2.64	1.20	90	6.3	20/Ctn/25 kg /1.2'	2
AT-53583	3/8"	1/2	12	160	120	163	12.6	320	1/4"	3/8"	11	311	3.44	1.56	90	6.3	10/Ctn/17.3 kg /0.84'	2
AT-53584	1/2"	1/2	12	160	120	163	12.6	320	1/4"	3/8"	11	311	3.44	1.56	90	6.3	10/Ctn/17.3 kg /0.84'	2
AT-54523	3/8"	1/2	12	160	90	122	10.3	262	1/4"	3/8"	10	283	2.71	1.23	90	6.3	20/Ctn/26 kg /1.2'	3
AT-54524	1/2"	1/2	12	160	90	122	10.3	262	1/4"	3/8"	10	283	2.71	1.23	90	6.3	20/Ctn/26 kg /1.2'	3
AT-54543	3/8"	3/8	10	350	60	81	10.0	254	1/4"	3/8"	8	226	2.69	1.34	90	6.3	10/Ctn/14.8 kg /0.6'	2
AT-54544	1/2"	3/8	10	350	60	81	10.0	254	1/4"	3/8"	8	226	2.69	1.34	90	6.3	10/Ctn/14.8 kg /0.6'	2

AIR RATCHET WRENCH

AT-5251
3/8" Air ratchet wrench
AT-5250
1/4" Air ratchet wrench



AT-5257
3/8" Air ratchet wrench
AT-5256
1/4" Air ratchet wrench



AT-54553
3/8" Air impact ratchet wrench
AT-54552
1/4" Air impact ratchet wrench



AT-53563
3/8" Air ratchet wrench
AT-53562
1/4" Air ratchet wrench



AT-54563
3/8" Sealed head air ratchet wrench
AT-54562
1/4" Sealed head air ratchet wrench



AT-54573
3/8" Sealed head air ratchet wrench
AT-54572
1/4" Sealed head air ratchet wrench



AT-53563M
3/8" Extended air ratchet wrench
AT-53562M
1/4" Extended air ratchet wrench



AT-53563L
3/8" Extended air ratchet wrench
AT-53562L
1/4" Extended air ratchet wrench



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5250	1/4"	5/32	4	260	15	20	5.12	130	1/4"	1/4"	5	142	0.99	0.45	90	6.3	20/Ctn/11 kg /0.3'	2
AT-5251	3/8"	5/32	4	260	15	20	5.12	130	1/4"	1/4"	5	142	0.99	0.45	90	6.3	20/Ctn/11 kg /0.3'	2
AT-5256	1/4"	3/16	5	260	25	34	6.69	170	1/4"	1/4"	6	170	1.15	0.52	90	6.3	20/Ctn/12 kg /0.3'	2
AT-5257	3/8"	3/16	5	260	25	34	6.69	170	1/4"	1/4"	6	170	1.15	0.52	90	6.3	20/Ctn/12 kg /0.3'	2
AT-53562	1/4"	1/4	6	280	30	41	7.00	178	1/4"	3/8"	7	198	1.21	0.55	90	6.3	10/Ctn/9.5 kg /0.58'	2
AT-53562L	1/4"	1/4	6	280	30	41	10.90	275	1/4"	3/8"	7	198	1.80	0.81	90	6.3	10/Ctn/9.5 kg /0.58'	2
AT-53562M	1/4"	1/4	6	280	30	41	8.60	218	1/4"	3/8"	7	198	1.46	0.66	90	6.3	20/Ctn/14.8 kg /0.69'	2
AT-53563	3/8"	1/4	6	280	35	47	7.00	178	1/4"	3/8"	7	198	1.21	0.55	90	6.3	10/Ctn/9.5 kg /0.58'	2
AT-53563L	3/8"	1/4	6	280	35	47	10.90	275	1/4"	3/8"	7	198	1.80	0.81	90	6.3	10/Ctn/9.5 kg /0.58'	2
AT-53563M	3/8"	1/4	6	280	35	47	8.60	218	1/4"	3/8"	7	198	1.46	0.66	90	6.3	20/Ctn/14.8 kg /0.69'	2
AT-54552	1/4"	3/16	5	650	25	34	6.30	160	1/4"	3/8"	6	170	1.43	0.65	90	6.3	20/Ctn/14.6 kg /0.48'	2
AT-54553	3/8"	3/16	5	650	25	34	6.30	160	1/4"	3/8"	6	170	1.43	0.65	90	6.3	20/Ctn/14.6 kg /0.48'	2
AT-54562	1/4"	1/4	6	280	30	41	7.00	178	1/4"	3/8"	7	198	1.38	0.63	90	6.3	20/Ctn/14.1 kg /0.6'	2
AT-54563	3/8"	1/4	6	280	35	47	7.00	178	1/4"	3/8"	7	198	1.38	0.63	90	6.3	20/Ctn/14.1 kg /0.6'	2
AT-54572	1/4"	3/16	4	300	20	27	5.43	138	1/4"	3/8"	6	170	1.08	0.49	90	6.3	20/Ctn/11.4 kg /0.38'	2
AT-54573	3/8"	3/16	4	300	20	27	5.43	138	1/4"	3/8"	6	170	1.08	0.49	90	6.3	20/Ctn/11.4 kg /0.38'	2

AIR RATCHET BOX WRENCH



AT-5110 Series
AT-5110-06 6mm
AT-5110-07 7mm
AT-5110-08 8mm
AT-5110-09 9mm
AT-5110-10 10mm
AT-5110-11 11mm
AT-5110-12 12mm



AT-5111 Series
AT-5111-10 10mm
AT-5111-11 11mm
AT-5111-12 12mm
AT-5111-13 13mm
AT-5111-14 14mm



AT-5112 Series
AT-5112-15 15mm
AT-5112-16 16mm
AT-5112-17 17mm
AT-5112-18 18mm
AT-5112-19 19mm



AT-5113 Series
AT-5113-21 21mm
AT-5113-22 22mm
AT-5113-23 23mm
AT-5113-24 24mm
AT-5113-26 26mm
AT-5113-27 27mm



AT-5114 Series
AT-5114-29 29mm
AT-5114-30 30mm
AT-5114-32 32mm



AT-5115 Series
AT-5115-36 36mm



AT-5116 Series (Bent head type)
 Air ratchet box wrench
AT-5116-06 6mm
AT-5116-07 7mm
AT-5116-08 8mm
AT-5116-09 9mm
AT-5116-10 10mm
AT-5116-11 11mm
AT-5116-12 12mm



AT-5117 Series (Bent head type)
 Air ratchet box wrench
AT-5117-15 15mm
AT-5117-16 16mm
AT-5117-17 17mm
AT-5117-18 18mm
AT-5117-19 19mm



AT-5116R Series (Bent head type)
 Air ratchet box wrench - Left rotation
AT-5116R-06 6mm
AT-5116R-07 7mm
AT-5116R-08 8mm
AT-5116R-09 9mm
AT-5116R-10 10mm
AT-5116R-11 11mm
AT-5116R-12 12mm



Model No.	A		B		C		D		E		F	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
AT-5110	20.0	0.79	13.2	0.52	20	0.79	10.2	0.40	38.2	1.50	88.2	3.47
AT-5111	25.2	0.99	18	0.71	26	1.02	12.2	0.48	44.4	1.75	109.0	4.29
AT-5112	33.2	1.31	18	0.71	26	1.02	16.6	0.65	51.0	2.01	115.0	4.53
AT-5113	41.0	1.61	18	0.71	26	1.02	20.5	0.81	59.0	2.32	123.0	4.84
AT-5114	48.0	1.89	18	0.71	26	1.02	24.0	0.94	66.0	2.60	130.0	5.12
AT-5115	52.0	2.05	18	0.71	26	1.02	26.0	1.02	70.0	2.76	134.0	5.28
AT-5116(R)	20.0	0.79	13.2	0.52	20	0.79	10.2	0.40	38.2	1.50	83.9	3.30
AT-5117	25.2	0.99	18	0.71	26	1.02	12.2	0.48	44.4	1.75	105.0	4.10

FEATURES :

- The ratchet wrench can be used in narrow working spaces and can fasten bolts and nuts easily. This special tool can be reached tight place that other air tools can not.
- Remove: loosen nut by wrench then take nut out with air ratchet.
- Fasten: Press the trigger to position the nut or bolt, then tighten it with a torque wrench.

SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Hex. Box size mm	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight	
			ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg
AT-5110	6, 7, 8, 9, 10, 11, 12	180	10	13.6	11.02	280	1/4"	3/8"	6	170	2.82	1.28
AT-5111	10, 11, 12, 13, 14	200	18	25	13.39	340	1/4"	3/8"	8	226	4.21	1.91
AT-5112	15, 16, 17, 18, 19	150	60	81	15.35	390	1/4"	3/8"	12	340	5.33	2.42
AT-5113	21, 22, 23, 24, 26, 27	130	66	90	15.66	398	1/4"	3/8"	12	340	5.46	2.48
AT-5114	29, 30, 32	110	66	90	16.02	407	1/4"	3/8"	12	340	5.51	2.50
AT-5115	36	100	66	90	16.14	410	1/4"	3/8"	12	340	5.55	2.52
AT-5116(R)	6, 7, 8, 9, 10, 11, 12	220	18	25	12.88	327	1/4"	3/8"	8	226	4.23	1.92
AT-5117	15, 16, 17, 18, 19	190	18	25	13.11	333	1/4"	3/8"	8	226	4.40	2.00