

AIR IMPACT SCREWDRIVER (PISTOL TYPE)

AT-4077
Air impact screwdriver



AT-4078
Air impact screwdriver



AT-4176
Air impact screwdriver



AT-4179
Air impact screwdriver



AT-4069
Air impact screwdriver



AT-4175
Air impact screwdriver



AT-4071
Air impact screwdriver



AT-4074
Air impact screwdriver



AT-4068
Air impact screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4068	1/4	6.35	3/16	4~5	10000	30	41	6.10	155	1/4"	5/16"	7.0	198	1.98	0.90	90	6.3	15/Ctn/16kg/1.3'	2
AT-4069	1/4	6.35	1/4	6	7000	50	68	7.09	180	1/4"	5/16"	7.0	198	2.64	1.20	90	6.3	10/Ctn/14kg/0.9'	2
AT-4071	1/4	6.35	1/4	6~8	10000	65	88	6.10	155	1/4"	5/16"	7.5	212	3.04	1.38	90	6.3	10/Ctn/17kg/1.3'	2
AT-4074	1/4	6.35	3/16	4~5	11000	30	41	6.10	155	1/4"	5/16"	7.0	198	1.98	0.90	90	6.3	15/Ctn/16kg/1.3'	2
AT-4077	1/4	6.35	5/16	6~8	9000	70	95	6.38	162	1/4"	3/8"	10.0	283	2.64	1.20	90	6.3	10/Ctn/13.7kg/0.9'	3
AT-4078	1/4	6.35	5/16	8~10	9000	85	115	6.38	162	1/4"	3/8"	10.0	283	2.73	1.24	90	6.3	10/Ctn/14.1kg/0.9'	3
AT-4175	1/4	6.35	5/16	8	9500	80	108	6.10	155	1/4"	3/8"	9.0	255	3.13	1.42	90	6.3	10/Ctn/16kg/1.26'	3
AT-4176	1/4	6.35	1/2	12	12000	140	190	5.71	145	1/4"	3/8"	10.0	283	3.53	1.60	90	6.3	10/Ctn/17.5kg/0.83'	3
AT-4179	1/4	6.35	5/16	8	8000	75	102	7.32	186	1/4"	3/8"	7.0	198	2.78	1.26	90	6.3	10/Ctn/14.5kg/0.9'	2

AIR IMPACT SCREWDRIVER (STRAIGHT TYPE)

AT-4265
Air impact screwdriver



AT-4266
Air impact screwdriver



AT-4161
Air butterfly impact screwdriver



AT-4070A
Air impact screwdriver



AT-4267
Air impact screwdriver



AT-4260
Air butterfly impact screwdriver



AT-4362
Angle impact screwdriver



AT-4262
Angle impact screwdriver



AT-4060
AT-4060A
Air impact screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Working Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4060	1/4	6.35	3/16	4~5	11000	25	34	7.00	178	1/4"	5/16"	5.0	142	1.54	0.70	90	6.3	20/Ctn/16kg/1.1'	2
AT-4060A	1/4	6.35	3/16	4~5	11000	25	34	7.28	185	1/4"	5/16"	5.0	142	1.59	0.72	90	6.3	20/Ctn/16kg/1.1'	2
AT-4070A	1/4	6.35	1/4	6	7000	50	68	8.86	220	1/4"	5/16"	7.5	212	2.34	1.06	90	6.3	20/Ctn/25kg/1.1'	2
AT-4161	1/4	6.35	5/16	6~8	9500	60	81	6.50	165	1/4"	5/16"	8.5	241	2.30	1.05	90	6.3	20/Ctn/25kg/1.72'	2
AT-4260	1/4	6.35	3/16	5	10000	30	41	6.38	182	1/4"	5/16"	8.0	226	1.68	0.76	90	6.3	20/Ctn/17kg/0.7'	2
AT-4262	1/4	6.35	3/16	4~5	7500	20	27	9.17	233	1/4"	5/16"	6.0	170	2.69	1.22	90	6.3	20/Ctn/26 kg /1.9'	2
AT-4265	1/4	6.35	5/16	6~8	9000	70	95	8.66	220	1/4"	5/16"	7.0	198	2.51	1.14	90	6.3	20/Ctn/25Kg/0.88'	2
AT-4266	1/4	6.35	5/16	8	9000	85	115	8.66	220	1/4"	5/16"	7.0	198	2.60	1.18	90	6.3	20/Ctn/26Kg/0.88'	2
AT-4267	1/4	6.35	5/16	8	8800	80	108	7.95	202	1/4"	5/16"	8.0	226	2.34	1.06	90	6.3	20/Ctn/25kg/1.1'	2
AT-4362	1/4	6.35	1/4	5~6	8500	30	41	10.40	265	1/4"	5/16"	7.5	212	3.44	1.56	90	6.3	10/Ctn/18.6kg/1.1'	2

CUSHION CLUTCH AIR SCREWDRIVER



AT-4282

External adjustable clutch
air screwdriver (1600rpm)

AT-4283

External adjustable clutch
air screwdriver (750rpm)



AT-4284

External adjustable clutch
air screwdriver (1700rpm)

AT-4285

External adjustable clutch
air screwdriver (750rpm)



AT-4286

External adjustable clutch
air screwdriver (1800rpm)

AT-4287

External adjustable clutch
air screwdriver (800rpm)



AT-4188

External adjustable clutch
air screwdriver (1500rpm)



AT-4186

Adjustable clutch
air screwdriver (1800rpm)

AT-4187

Adjustable clutch
air screwdriver (800rpm)



AT-4080

Adjustable clutch
air screwdriver (1800rpm)

AT-4080A

Adjustable clutch
air screwdriver (800rpm)



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		in-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4080	1/4	6.35	3/16	M5	1800	55-115	6.2~13	8.27	210	1/4"	3/8"	12.0	340	2.51	1.14	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4080A	1/4	6.35	1/4	M6	800	55-145	6.2~16.4	8.86	225	1/4"	3/8"	12.0	340	2.91	1.32	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4186	1/4	6.35	3/16	M5	1800	55-115	6.2~13	8.34	212	1/4"	3/8"	10.0	283	2.27	1.03	90	6.3	10/Ctn/13Kg/0.91'	3
AT-4187	1/4	6.35	1/4	M6	800	55-145	6.2~16.4	8.86	225	1/4"	3/8"	10.0	283	2.71	1.23	90	6.3	10/Ctn/14Kg/0.91'	3
AT-4188	1/4	6.35	5/32	M4	1500	36	4.0	7.48	190	1/4"	3/8"	6.5	184	2.20	1.00	90	6.3	10/Ctn/13.5Kg/0.91'	3
AT-4282	1/4	6.35	5/32	M4	1600	55-85	6.2~9.6	6.46	164	1/4"	3/8"	6.5	184	1.87	0.85	90	6.3	10/Ctn/11Kg/0.91'	3
AT-4283	1/4	6.35	5/32	M4	750	40-85	4.5~9.6	6.46	164	1/4"	3/8"	6.5	184	1.87	0.85	90	6.3	10/Ctn/11Kg/0.91'	3
AT-4284	1/4	6.35	3/16	M5	1700	55-105	6.2~11.9	6.97	177	1/4"	3/8"	7.5	212	2.73	1.24	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4285	1/4	6.35	3/16	M5	750	45-115	5.1~13	6.97	177	1/4"	3/8"	7.5	212	2.73	1.24	90	6.3	10/Ctn/15Kg/0.91'	3
AT-4286	1/4	6.35	3/16	M5	1800	40-90	4.5-10.2	8.66	220	1/4"	3/8"	10.0	283	2.53	1.15	90	6.3	10/Ctn/13Kg/0.91'	3
AT-4287	1/4	6.35	1/4	M5	800	40-105	4.5-11.9	9.25	235	1/4"	3/8"	10.0	283	2.91	1.32	90	6.3	10/Ctn/14.5Kg/0.91'	3

CUSHION CLUTCH AIR SCREWDRIVER



AT-4155
External adjustable clutch
air screwdriver (1800rpm)



AT-4058
External adjustable clutch
air screwdriver (800 rpm)
AT-4059
External adjustable clutch
air screwdriver (1400 rpm)



AT-4154
External adjustable clutch
air screwdriver (600 rpm)
AT-4153
External adjustable clutch
air screwdriver (1600 rpm)



AT-4050A
Cushion clutch air screwdriver



AT-4050
Cushion clutch air screwdriver



AT-4051A
Cushion clutch air screwdriver



AT-4085
Cushion clutch air screwdriver



AT-4151
External adjustable clutch
air screwdriver (800 rpm)
AT-4152
External adjustable clutch
air screwdriver (1400 rpm)



AT-4052
Cushion clutch angle air screwdriver



Model No.	Hex. Shank Size		Capacity bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		in-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-4050	1/4	6.35	3/32	2.5	1700	18	2.0	9.25	235	1/4"	1/4"	5.5	156	1.34	0.61	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4050A	1/4	6.35	3/32	2.5	1700	18	2.0	9.25	235	1/4"	1/4"	5.5	156	1.34	0.61	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4051A	1/4	6.35	1/8	3.0	1800	22	2.5	8.66	220	1/4"	1/4"	4.5	127	1.37	0.62	90	6.3	20/Ctn/14Kg/1.1'	1.5
AT-4052	1/4	6.35	1/8	3.0	1600	22	2.5	9.25	230	1/4"	1/4"	5.0	142	1.68	0.76	90	6.3	20/Ctn/19Kg/1.4'	1.5
AT-4058	1/4	6.35	5/32	4.0	800	44	5.0	10.98	279	1/4"	1/4"	5.0	141	2.14	0.97	90	6.3	20/Ctn/22Kg/1.4'	1.5
AT-4059	1/4	6.35	5/32	4.0	1450	36	4.0	10.98	279	1/4"	1/4"	5.0	141	2.14	0.97	90	6.3	20/Ctn/22Kg/1.4'	1.5
AT-4085	1/4	6.35	3/16	5.0	1800	115	13.0	10.43	265	1/4"	5/16"	7.5	212	2.56	1.16	90	6.3	10/Ctn/14Kg/0.6'	2
AT-4151	1/4	6.35	5/32	4.0	800	62	7.0	13.15	334	1/4"	1/4"	5.0	141	2.76	1.25	90	6.3	10/Ctn/16Kg/0.8'	1.5
AT-4152	1/4	6.35	5/32	4.0	1400	62	7.0	13.15	334	1/4"	1/4"	5.0	141	2.76	1.25	90	6.3	10/Ctn/16Kg/0.8'	1.5
AT-4153	1/4	6.35	5/32	4.0	1600	30~65	3.4~7.3	10.35	263	1/4"	5/16"	7.5	212	2.49	1.13	90	6.3	10/Ctn/13.5kg/0.6'	2
AT-4154	1/4	6.35	3/16	5.0	600	30~97	3.4~11	11.06	281	1/4"	5/16"	7.5	212	2.71	1.28	90	6.3	10/Ctn/15kg/0.6'	2
AT-4155	1/4	6.35	1/8	3.0	1800	22	2.5	8.98	228	1/4"	1/4"	4.0	113	1.68	0.76	90	6.3	20/Ctn/20.7Kg/1.1'	1.5

AIR SHUT-OFF CLUTCH SCREWDRIVER



AT-4112

Pistol type shut-off air screwdriver (800 rpm)

AT-4113

Pistol type shut-off air screwdriver (1450 rpm)



AT-4116

Pistol type shut-off air screwdriver (390 rpm)



AT-4110

Lever to start shut-off
air screwdriver (800 rpm)

AT-4111

Lever to start shut-off
air screwdriver (1450 rpm)



AT-4010

Push to start shut-off
air screwdriver (2500 rpm)

AT-4011

Push to start shut-off
air screwdriver (750 rpm)



AT-4010H

Push to start shut-off
air screwdriver (2500 rpm)

AT-4011H

Push to start shut-off
air screwdriver (750 rpm)



AT-4013

Push to start shut-off air screwdriver
(1000 rpm)



AT-4014

Push to start shut-off
air screwdriver (950 rpm)

AT-4015

Push to start shut-off
air screwdriver (650 rpm)



AT-4114

Angle type shut-off
air screwdriver (800 rpm)

AT-4115

Angle type shut-off
air screwdriver (1450 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size mm	Free Speed RPM	Torque Range		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuf (kg)	Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg		
AT-4010	5/32	4	2	2500	1.8-3.1	0.2~0.35	7.00	178	1/4"	1/4"	3	85	0.77	0.35	10/Ctn/7Kg/0.9'	1.5
AT-4010H	1/4	6.35	2	2500	1.8-3.1	0.2~0.35	7.28	185	1/4"	1/4"	3	85	0.55	0.25	20/Ctn/8Kg/0.9'	1.5
AT-4011	5/32	4	2.5	750	3.1~8.9	0.35~1.0	7.48	190	1/4"	1/4"	3	85	0.82	0.37	10/Ctn/7Kg/0.9'	1.5
AT-4011H	1/4	6.35	2.5	750	3.1~8.9	0.35~1.0	7.60	192	1/4"	1/4"	3	85	0.60	0.27	20/Ctn/8.5Kg/0.9'	1.5
AT-4013	1/4	6.35	3.5	1000	10.6~19.5	1.2~2.2	8.98	228	1/4"	1/4"	4	113	1.54	0.70	20/Ctn/14Kg/1.4'	2
AT-4014	1/4	6.35	4~5	950	17.7~42.5	2.0~4.8	9.84	250	1/4"	1/4"	4	113	2.05	0.93	10/Ctn/12Kg/1.2'	2
AT-4015	1/4	6.35	5~6	650	26.6~62	3.0~7.0	9.84	250	1/4"	1/4"	4	113	2.05	0.93	10/Ctn/12Kg/1.2'	2
AT-4110	1/4	6.35	4	800	14.2~27.5	1.6~3.1	11.22	285	1/4"	1/4"	4	113	2.09	0.95	10/Ctn/12Kg/1.2'	2
AT-4111	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	11.22	285	1/4"	1/4"	4	113	2.09	0.95	10/Ctn/12Kg/1.2'	2
AT-4112	1/4	6.35	4	800	14.2~27.5	1.6~3.1	7.68	195	1/4"	1/4"	4	113	2.16	0.98	10/Ctn/12Kg/1.2'	2
AT-4113	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	7.68	195	1/4"	1/4"	4	113	2.16	0.98	10/Ctn/12Kg/1.2'	2
AT-4114	1/4	6.35	5	800	19.5~38.1	2.2~4.3	13.39	340	1/4"	1/4"	4	113	2.69	1.22	10/Ctn/14Kg/1.2'	2
AT-4115	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	13.39	340	1/4"	1/4"	4	113	2.69	1.22	10/Ctn/14Kg/1.2'	2
AT-4116	1/4	6.35	6	390	40~88	4.5~10.0	8.86	225	1/4"	1/4"	4	113	2.53	1.15	10/Ctn/14Kg/1.2'	2

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

AIR SHUT-OFF CLUTCH SCREWDRIVER PISTOL TYPE



AT-4016P15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016P11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017P16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017P09

Shut-off clutch air screwdriver (900 rpm)



AT-4018P30

Shut-off clutch air screwdriver (3,000 rpm)

AT-4018P20

Shut-off clutch air screwdriver (2,000 rpm)

AT-4018P11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4019P07

Shut-off clutch air screwdriver (700 rpm)

AT-4019P05

Shut-off clutch air screwdriver (500 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Torque Range		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016P15	1/4	6.35	M2	1500	3.5~6.2	0.4~0.7	8.58	218	1/4"	1/4"	4	113	1.54	0.7	70	5.0	2
AT-4016P11	1/4	6.35	M2	1100	3.5~8.8	0.4~1.0	8.58	218	1/4"	1/4"	4	113	1.54	0.7	70	5.0	2
AT-4017P16	1/4	6.35	M2~M3	1600	6.2~11.5	0.7~1.3	8.31	211	1/4"	1/4"	4	113	1.98	0.9	70	5.0	2
AT-4017P09	1/4	6.35	M3	900	6.2~17.7	0.7~2.0	8.31	211	1/4"	1/4"	4	113	1.98	0.9	70	5.0	2
AT-4018P30	1/4	6.35	M3~M4	3000	7.1~27	0.8~3.0	7.79	198	1/4"	1/4"	5	141	2.35	1.07	85	6.0	2
AT-4018P20	1/4	6.35	M3~M4	2000	7.1~40	0.8~4.5	7.79	198	1/4"	1/4"	5	141	2.35	1.07	85	6.0	2
AT-4018P11	1/4	6.35	M3~M5	1100	10.6~53	1.2~6.0	7.79	198	1/4"	1/4"	5	141	2.35	1.07	85	6.0	2
AT-4019P07	1/4	6.35	M4~M5	700	35~80	4.0~9.0	8.98	228	1/4"	1/4"	5	141	2.68	1.22	85	6.0	2
AT-4019P05	1/4	6.35	M4~M6	500	35~97	4.0~11.0	8.98	228	1/4"	1/4"	5	141	2.68	1.22	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / PUSH START



AT-4016S15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016S11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017S16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017S09

Shut-off clutch air screwdriver (900 rpm)



AT-4018S30

Shut-off clutch air screwdriver (3,000 rpm)

AT-4018S20

Shut-off clutch air screwdriver (2,000 rpm)

AT-4018S11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4019S07

Shut-off clutch air screwdriver (700 rpm)

AT-4019S05

Shut-off clutch air screwdriver (500 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Torque Range		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016S15	1/4	6.35	M2	1500	3.5~6.2	0.4~0.7	8.5	216	1/8"	1/4"	4	113	0.77	0.35	70	5.0	2
AT-4016S11	1/4	6.35	M2	1100	3.5~8.8	0.4~1.0	8.5	216	1/8"	1/4"	4	113	0.77	0.35	70	5.0	2
AT-4017S16	1/4	6.35	M2-M3	1600	6.2~11.5	0.7~1.3	9.0	229	1/8"	1/4"	4	113	1.32	0.60	70	5.0	2
AT-4017S09	1/4	6.35	M3	900	6.2~17.7	0.7~2.0	9.0	229	1/8"	1/4"	4	113	1.32	0.60	70	5.0	2
AT-4018S30	1/4	6.35	M3-M4	3000	7.1~27	0.8~3.0	9.5	242	1/4"	1/4"	5	141	1.80	0.82	85	6.0	2
AT-4018S20	1/4	6.35	M3-M4	2000	7.1~40	0.8~4.5	9.5	242	1/4"	1/4"	5	141	1.80	0.82	85	6.0	2
AT-4018S11	1/4	6.35	M3-M5	1100	10.6~53	1.2~6.0	9.5	242	1/4"	1/4"	5	141	1.80	0.82	85	6.0	2
AT-4019S07	1/4	6.35	M4-M5	700	35~80	4.0~9.0	10.7	272	1/4"	1/4"	5	141	2.11	0.96	85	6.0	2
AT-4019S05	1/4	6.35	M4-M6	500	35~97	4.0~11.0	10.7	272	1/4"	1/4"	5	141	2.11	0.96	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / LEVER START



AT-4016L15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016L11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017L16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017L09

Shut-off clutch air screwdriver (900 rpm)



AT-4018L30

Shut-off clutch air screwdriver (3,000 rpm)

AT-4018L20

Shut-off clutch air screwdriver (2,000 rpm)

AT-4018L11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4019L07

Shut-off clutch air screwdriver (700 rpm)

AT-4019L05

Shut-off clutch air screwdriver (500 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Torque Range		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016L15	1/4	6.35	M2	1500	3.5~6.2	0.4~0.7	9.37	238	1/8"	1/4"	4	113	0.90	0.41	70	5.0	2
AT-4016L11	1/4	6.35	M2	1100	3.5~8.8	0.4~1.0	9.37	238	1/8"	1/4"	4	113	0.90	0.41	70	5.0	2
AT-4017L16	1/4	6.35	M2~M3	1600	6.2~11.5	0.7~1.3	9.69	246	1/8"	1/4"	4	113	1.39	0.63	70	5.0	2
AT-4017L09	1/4	6.35	M3	900	6.2~17.7	0.7~2.0	9.69	246	1/8"	1/4"	4	113	1.39	0.63	70	5.0	2
AT-4018L30	1/4	6.35	M3~M4	3000	7.1~27	0.8~3.0	10.00	254	1/4"	1/4"	5	141	1.91	0.87	85	6.0	2
AT-4018L20	1/4	6.35	M3~M4	2000	7.1~40	0.8~4.5	10.00	254	1/4"	1/4"	5	141	1.91	0.87	85	6.0	2
AT-4018L11	1/4	6.35	M3~M5	1100	10.6~53	1.2~6.0	10.0	254	1/4"	1/4"	5	141	1.91	0.87	85	6.0	2
AT-4019L07	1/4	6.35	M4~M5	700	35~80	4.0~9.0	11.2	284	1/4"	1/4"	5	141	2.22	1.01	85	6.0	2
AT-4019L05	1/4	6.35	M4~M6	500	35~97	4.0~11.0	11.2	284	1/4"	1/4"	5	141	2.22	1.01	85	6.0	2

AIR SHUT-OFF CLUTCH SCREWDRIVER ANGLE TYPE



AT-4016A15

Shut-off clutch air screwdriver (1,500 rpm)

AT-4016A11

Shut-off clutch air screwdriver (1,100 rpm)



AT-4017A16

Shut-off clutch air screwdriver (1,600 rpm)

AT-4017A09

Shut-off clutch air screwdriver (900 rpm)



AT-4018A19

Shut-off clutch air screwdriver (1,900 rpm)

AT-4018A13

Shut-off clutch air screwdriver (1,300 rpm)

AT-4018A07

Shut-off clutch air screwdriver (700 rpm)



AT-4019A05

Shut-off clutch air screwdriver (480 rpm)

AT-4019A03

Shut-off clutch air screwdriver (320 rpm)



Model No.	Drive Size inch	Capacity bolt Size mm	Free Speed RPM	Torque Range		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
				in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²	
AT-4016A15	1/4" Hex.	M2	1500	3.5~6.2	0.4~0.7	11.2	284	1/8"	1/4"	4	113	1.23	0.56	70	5.0	2
AT-4016A11	1/4" Hex.	M2	1100	3.5~8.8	0.4~1.0	11.2	284	1/8"	1/4"	4	113	1.23	0.56	70	5.0	2
AT-4017A16	1/4" Hex.	M2~M3	1600	6.2~11.5	0.7~1.3	11.4	290	1/8"	1/4"	4	113	1.76	0.80	70	5.0	2
AT-4017A09	1/4" Hex.	M3	900	6.2~17.7	0.7~2.0	11.4	290	1/8"	1/4"	4	113	1.76	0.80	70	5.0	2
AT-4018A19	1/4" Hex.	M3~M4	1900	12.4~35	1.4~4.0	12.0	306	1/4"	1/4"	5	141	2.51	1.14	85	6.0	2
AT-4018A13	1/4" Hex.	M3~M5	1300	12.4~58	1.4~6.5	12.0	306	1/4"	1/4"	5	141	2.51	1.14	85	6.0	2
AT-4018A07	1/4" Hex.	M4~M5	700	17.7~71	2~8.0	12.0	306	1/4"	1/4"	5	141	2.51	1.14	85	6.0	2
AT-4019A05	1/4" Hex.	M5~M6	480	53~106	6~12	13.2	336	1/4"	1/4"	5	141	2.82	1.28	85	6.0	2
AT-4019A03	1/4" Hex.	M5~M6	320	53~133	6~15	13.2	336	1/4"	1/4"	5	141	2.82	1.28	85	6.0	2