

1" & 1-1/2" IMPACT WRENCH



AT-5088 1" Air impact wrench
AT-5088L 1" Air impact wrench w/8" anvil
AT-5089 1-1/2" Air impact wrench
AT-5089L 1-1/2" Air impact wrench w/8" anvil



FEATURES

- ✘ Twin hammer mechanism
- ✘ 4 position power settings
- ✘ Aluminum housing
- ✘ Max torque of 2,500 ft-lb



AT-5387 1" Composite air impact wrench
AT-5387L 1" Composite air impact wrench w/8" anvil



FEATURES

- ✘ Twin hammer mechanism
- ✘ Composite housing - best hand feeling
- ✘ Compact design with lightweight
- ✘ 3 position settings in forward and 1 in reverse
- ✘ Max torque of 2,200 ft-lb



AT-5186 1" Air impact wrench
AT-5186L 1" Air impact wrench w/8" anvil



FEATURES

- ✘ Twin hammer mechanism
- ✘ Regulator integrated in forward/reverse knob with 3 position power setting in both directions.
- ✘ Aluminum housing
- ✘ Max torque of 2,000 ft-lb



AT-5380 1" Air impact wrench
AT-5380-6 1" Air impact wrench w/6" anvil



FEATURES

- ✘ Twin hammer mechanism
- ✘ Compact design with lightweight
- ✘ Regulator integrated in forward/reverse knob with 3 position power setting in both directions.
- ✘ Aluminum housing
- ✘ Max torque of 1,600 ft-lb

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5088	1"	2	50	3000	2500	3390	16.93	430	1/2"	1/2"	24	679	33.28	15.10	90-115	6.3-8	1/Ctn/18.7 kg/1.5'	7.5
AT-5088L	1"	2	50	3000	2500	3390	24.80	630	1/2"	1/2"	24	679	37.16	16.86	90-115	6.3-8	1/Ctn/20.5 kg/1.5'	7.5
AT-5089	1 1/2"	2	50	3000	2500	3390	16.93	430	1/2"	1/2"	24	679	34.82	15.80	90-115	6.3-8	1/Ctn/19.3 kg/1.5'	7.5
AT-5089L	1 1/2"	2	50	3000	2500	3390	24.80	630	1/2"	1/2"	24	679	41.44	18.80	90-115	6.3-8	1/Ctn/24 kg/1.5'	7.5
AT-5186	1"	1 1/2	38	4000	2000	2710	15.00	381	1/2"	1/2"	25	708	20.50	9.30	90-115	6.3-8	2/Ctn/21.2 kg/1.47'	7.5
AT-5186L	1"	1 1/2	38	4000	2000	2710	21.10	536	1/2"	1/2"	25	708	23.60	10.60	90-115	6.3-8	2/Ctn/23.8 kg/1.47'	7.5
AT-5380	1"	1 3/8	36	5000	1600	2170	14.57	370	1/2"	1/2"	19	538	16.31	7.40	90-115	6.3-8	2/Ctn/17 kg/1.28'	7.5
AT-5380-6	1"	1 3/8	36	5000	1600	2170	19.17	487	1/2"	1/2"	19	538	17.86	8.10	90-115	6.3-8	2/Ctn/19 kg/1.28'	7.5
AT-5387	1"	1 5/8	42	5000	2200	2983	16.70	425	1/2"	1/2"	20	566	13.70	6.20	90-115	6.3-8	2/Ctn/14.5 kg/1.8'	7.5
AT-5387L	1"	1 5/8	42	5000	2200	2983	25.00	635	1/2"	1/2"	20	566	13.70	7.60	90-115	6.3-8	2/Ctn/17.3 kg/1.8'	7.5

L : with 8" anvil -6 : with 6" anvil

1" IMPACT WRENCH

AT-5186P 1" Air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Aluminum housing
- ✧ Max torque of 1,800 ft-lb
- ✧ Regulator integrated in forward/reverse knob with 3 position power setting in both directions.

AT-5387P 1" Composite air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Lightweight composite housing
- ✧ Max torque of 2,000 ft-lb
- ✧ 3 position settings in forward and 1 in reverse

AT-5285P 1" Air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Aluminum housing
- ✧ Max torque of 1,100 ft-lb
- ✧ 6 position power settings

AT-5380P 1" Air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Aluminum housing
- ✧ Max torque of 1,600 ft-lb
- ✧ Regulator integrated in forward/reverse knob with 3 position power setting in both directions.

AT-5386P 1" Air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Max torque of 1,200 ft-lb
- ✧ 3 position power settings
- ✧ Combined power regulator with forward/reverse
- ✧ Aluminum housing

AT-5388P 1" Composite air impact wrench



FEATURES

- ✧ Twin hammer mechanism
- ✧ Lightweight composite housing
- ✧ Max torque of 1,100 ft-lb
- ✧ 3 position settings in forward and 1 in reverse

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5186P	1"	1 ³ / ₈	36	3500	1800	2441	11.81	300	1/2"	1/2"	23.5	665	21.20	9.60	90~115	6.3~8	2/Ctn/22 kg/1.35'	7.5
AT-5285P	1"	1 ¹ / ₄	30	5500	1100	1492	8.50	216	3/8"	1/2"	16.0	453	13.60	6.15	90	6.3	4/Ctn/25.5 kg/1.3'	5
AT-5380P	1"	1 ³ / ₈	36	5000	1600	2170	10.82	275	1/2"	1/2"	18.0	509	16.30	7.40	90~115	6.3~8	2/Ctn/17.2 kg/1.24'	7.5
AT-5387P	1"	1 ¹ / ₂	38	5000	2000	2170	10.00	256	1/2"	1/2"	20.0	566	12.30	5.60	90~115	6.3~8	2/Ctn/13 kg/1.35'	7.5
AT-5386P	1"	1 ¹ / ₄	32	4500	1200	1627	8.74	222	3/8"	1/2"	14.0	396	11.24	5.10	90	6.3	4/Ctn/23.5 kg/1.3'	5
AT-5388P	1"	1 ¹ / ₈	28	5500	1100	1492	8.22	219	3/8"	1/2"	16.0	453	6.94	3.15	90	6.3	4/Ctn/15 kg/1.3'	5

P : pistol type

3/4" IMPACT WRENCH

AT-5069 3/4" Air impact wrench
AT-5069-4 3/4" Air impact wrench w/4" anvil



FEATURES

- * Twin hammer mechanism
- * Max torque of 950 ft-lb
- * 4 position power settings
- * Convenient reverse valve

AT-5165 3/4" Air impact wrench



FEATURES

- * Twin hammer mechanism
- * Max torque of 1000 ft-lb
- * 6 position power settings
- * Aluminum housing

AT-5269 3/4" Composite Air impact wrench



FEATURES

- * Twin hammer mechanism
- * Lightweight composite housing
- * Max torque of 1,000 ft-lb
- * 3 position settings in forward and 1 in reverse

AT-5169 3/4" Composite air impact wrench



FEATURES

- * Twin hammer mechanism
- * Lightweight composite housing
- * Max torque of 1,000 ft-lb
- * 3 position settings in forward and 1 in reverse

AT-5066 3/4" Air impact wrench
AT-5066L 3/4" Air impact wrench w/6" anvil



FEATURES

- * Twin hammer mechanism
- * Max torque of 800 ft-lb
- * 2 position power settings
- * Combined power regulator with forward/reverse
- * Aluminum housing

AT-5266 3/4" Air impact wrench



FEATURES

- * Twin hammer mechanism
- * Max torque of 1200 ft-lb
- * 3 position power settings
- * Combined power regulator with forward/reverse
- * Aluminum housing

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5066	3/4"	1	25	6500	800	1085	8.98	228	1/4"	3/8"	14	396	10.00	4.55	90	6.3	4/Ctn/20.7 kg/1.32'	5
AT-5066L	3/4"	1	25	6500	800	1085	13.78	350	1/4"	3/8"	14	396	11.20	5.10	90	6.3	4/Ctn/23.6 kg/1.48'	5
AT-5069	3/4"	1 1/8	28	4000	950	1288	12.60	320	3/8"	1/2"	19	538	11.20	5.10	90	6.3	4/Ctn/22.5 kg/1.5'	5
AT-5069-4	3/4"	1 1/8	28	4000	950	1288	14.37	365	3/8"	1/2"	19	538	11.60	5.25	90	6.3	4/Ctn/23.5 kg/1.5'	5
AT-5165	3/4"	1 1/4	30	5500	1000	1356	8.50	216	3/8"	1/2"	16	453	13.55	6.15	90	6.3	4/Ctn/25.5 kg/1.3'	5
AT-5169	3/4"	1 1/8	28	5500	1000	1356	9.25	235	3/8"	3/8"	16	453	8.00	3.64	90	6.3	4/Ctn/17 kg/1.32'	5
AT-5266	3/4"	1 1/4	32	4500	1200	1627	8.46	215	3/8"	3/8"	14	396	11.00	5.00	90	6.3	4/Ctn/23.0 kg/1.32'	5
AT-5269	3/4"	1 1/8	28	5500	1000	1356	8.00	202	3/8"	3/8"	16	455	6.60	3.00	90	6.3	4/Ctn/14.0 kg/1.28'	5

L : with 6" anvil -4 : with 4" anvil

3/4" IMPACT WRENCH

AT-5264
3/4" Composite air impact wrench



AT-5067
3/4" Air impact wrench



AT-5065
3/4" Air impact wrench



AT-5061
3/4" Air impact wrench



AT-5060
3/4" Air impact wrench



AT-5061K 14 pcs 3/4" impact wrench kit
AT-5060K 14 pcs 3/4" impact wrench kit



AT-5065K 14 pcs 3/4" impact wrench kit



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-5060	3/4"	3/4	18	4500	500	678	9.49	241	1/4"	3/8"	14.5	410	10.2	4.52	90	6.3	4/Ctn/20.0 kg/1.23'	5
AT-5061	3/4"	1	25	4800	800	1085	9.84	250	1/4"	3/8"	14.0	396	10.4	4.70	90	6.3	4/Ctn/21.0 kg/1.23'	5
AT-5065	3/4"	1	25	4800	800	1085	9.45	240	1/4"	3/8"	14.5	410	11.0	4.98	90	6.3	4/Ctn/22.3 kg/1.23'	5
AT-5067	3/4"	3/4	18	6800	700	950	8.66	220	1/4"	3/8"	15.0	425	6.4	2.96	90	6.3	8/Ctn/26.2 kg/1.2'	3
AT-5264	3/4"	3/4	18	8500	700	950	7.80	198	1/4"	3/8"	13.0	368	4.1	1.85	90	6.3	8/Ctn/18.0 kg/1.2'	3

Model No.	AT-5060K	AT-5061K	AT-5065K
Contents	1 Pc AT-5060 8 Pcs Air Socket : 26,27,29,30,32,35, 36,38 mm 2 Pcs Hex. Wrench (4, 5 mm) 1 Pc Nipple 1 Pc Oil Pot 1 Pc Plastic Case Packing : 2 Sets/Ctn/18.5 kg/1.79'	1 Pc AT-5061 8 Pcs Air Socket : 26,27,29,30,32,35, 36,38 mm 2 Pcs Hex. Wrench (4, 5 mm) 1 Pc Nipple 1 Pc Oil Pot 1 Pc Plastic Case Packing : 2 Sets/Ctn/19 kg/1.79'	1 Pc AT-5065 8 Pcs Air Socket : 26,27,29,30,32,35, 36,38 mm 2 Pcs Hex. Wrench (4, 5 mm) 1 Pc Nipple 1 Pc Oil Pot 1 Pc Plastic Case Packing : 2 Sets/Ctn/20 kg/1.79'

K : kit

1/2" IMPACT WRENCH



AT-5348

1/2" Composite air impact wrench



FEATURES

- ✧ Lightweight composite housing
- ✧ 3 position settings in forward and 1 in reverse
- ✧ Handle exhaust



AT-5441

1/2" Composite air impact wrench



FEATURES

- ✧ Lightweight composite housing
- ✧ 3 position settings in forward and 1 in reverse
- ✧ Handle exhaust



AT-5744

1/2" Composite air impact wrench



FEATURES

- ✧ Lightweight composite housing
- ✧ Lightweight Magnesium alloy hammer case
- ✧ 3 position settings in forward and 1 in reverse
- ✧ Handle exhaust



AT-5743

1/2" Composite air impact wrench



FEATURES

- ✧ Lightweight composite housing
- ✧ Lightweight Magnesium alloy hammer case
- ✧ 3 position settings in forward and 1 in reverse
- ✧ Handle exhaust

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Continuous Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg		
AT-5348	1/2"	3/4	18	7500	700	950	7.83	199	1/4"	3/8"	13	368	4.40	2.00	10/Ctn/23.2 kg /1.57'	3
AT-5441	1/2"	1/2	12	11000	250	339	6.81	173	1/4"	3/8"	10	283	2.98	1.35	10/Ctn/15 kg /1.26'	3
AT-5743	1/2"	9/16	14	8500	350	475	5.59	142	1/4"	3/8"	11	311	2.20	1.00	10/Ctn/12 kg /1.26'	3
AT-5744	1/2"	3/4	18	8500	700	950	7.10	180	1/4"	3/8"	13	368	3.53	1.60	10/Ctn/19 kg /1.57'	3

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

1/2" IMPACT WRENCH


AT-5542
1/2" Air impact wrench



FEATURES

- * Aluminum housing
- * 3 position settings
- * Handle exhaust

AT-5148
1/2" Air impact wrench



FEATURES

- * Aluminum housing
- * 4 position settings
- * Handle exhaust

AT-5741
1/2" Air impact wrench



FEATURES

- * 2 position settings in forward and 1 in reverse
- * High efficient motor 20% more up. (Double Air Intake design)
- * Handle exhaust

AT-5044
1/2" Air impact wrench



FEATURES

- * Aluminum housing
- * 6 position settings
- * Front exhaust

AT-5640
1/2" Air impact wrench



FEATURES

- * Aluminum housing
- * 3 position settings
- * Special precise motor offers higher torque
- * Handle exhaust

AT-5343
1/2" Air impact wrench



FEATURES

- * Quick reversible trigger.
- * Aluminum housing
- * 4 position settings
- * Side exhaust

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Continuous Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cu.ft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg		
AT-5044	1/2"	5/8	16	7000	500	678	7.28	185	1/4"	3/8"	12	340	5.80	2.64	8/Ctn/23.6 kg /1.2'	3
AT-5148	1/2"	3/4	18	7000	700	950	7.76	197	1/4"	3/8"	15	425	6.31	2.86	8/Ctn/24.5 kg /1.2'	3
AT-5343	1/2"	5/8	16	6000	400	542	7.28	185	1/4"	3/8"	12	340	5.60	2.54	5/Ctn/14 kg /0.9'	3
AT-5542	1/2"	3/4	18	7500	700	950	7.00	178	1/4"	3/8"	12	340	5.78	2.62	8/Ctn/24 kg /1.3'	3
AT-5640	1/2"	3/4	18	9000	600	814	5.55	141	1/4"	3/8"	11	311	4.01	1.82	8/Ctn/17 kg /1'	3
AT-5741	1/2"	3/4	18	8000	600	814	6.10	155	1/4"	3/8"	20	566	3.96	1.80	10/Ctn/20 kg /1.57'	3

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

1/2" MINI AIR IMPACT WRENCH

AT-5648J
1/2" Mini air impact wrench



Handle exhaust

AT-5648T
1/2" Mini air impact wrench



Handle exhaust

AT-5344
1/2" Air impact wrench



Handle exhaust

AT-5641
1/2" Air impact wrench



Handle exhaust

AT-5746
1/2" Air impact wrench



Handle exhaust with muffler

AT-5446
1/2" Air impact wrench



Handle exhaust

AT-5042
1/2" Air impact wrench



Front exhaust

AT-5646
1/2" Air impact wrench



Side exhaust

AT-5740
1/2" Air impact wrench



Side exhaust

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Continuous Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg		
AT-5042	1/2"	1/2	13	9000	190	258	6.22	157	1/4"	3/8"	10	283	3.04	1.38	10/Ctn/16.2 kg /1'	3
AT-5344	1/2"	1/2	13	12000	300	407	5.71	145	1/4"	3/8"	10	283	3.53	1.60	10/Ctn/17.5 kg /0.83'	3
AT-5446	1/2"	1/2	13	9500	200	271	5.91	160	1/4"	3/8"	8	226	3.15	1.43	10/Ctn/16 kg/1.26'	3
AT-5641	1/2"	5/8	16	10000	480	651	4.45	113	1/4"	3/8"	10	283	3.31	1.50	10/Ctn/17 kg/0.9'	3
AT-5646	1/2"	1/2	13	9000	250	339	3.46	88	1/4"	3/8"	10	283	2.78	1.26	10/Ctn/15 kg/0.9'	3
AT-5648J	1/2"	5/8	16	10000	450	610	4.09	104	1/4"	3/8"	10	283	3.02	1.34	10/Ctn/16 kg/1'	3
AT-5648T	1/2"	5/8	16	10000	450	610	4.09	104	1/4"	3/8"	10	283	3.02	1.34	10/Ctn/16 kg/1'	3
AT-5740	1/2"	3/8	10	9000	160	217	7.95	202	1/4"	3/8"	8	226	2.65	1.20	20/Ctn/28.5 kg/1.1'	3
AT-5746	1/2"	3/8	10	8500	180	244	6.10	155	1/4"	3/8"	7	198	2.91	1.32	12/Ctn/16 kg/1'	3

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

1/2" IMPACT WRENCH

AT-5247
1/2" Air impact wrench



Handle exhaust

AT-5043
1/2" Air impact wrench



Front exhaust

AT-5041
1/2" Air impact wrench



Front exhaust

AT-5040
1/2" Air impact wrench



Front exhaust

AT-5004
AT-5005
17 pcs impact wrench kit



AT-5044K
17 pcs impact wrench kit



AT-5641K
AT-5648JK
AT-5648TK
18 pcs impact wrench kit



Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Continuous Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg		
AT-5040	1/2"	1/2	12	7000	230	312	7.00	178	1/4"	3/8"	13.5	382	4.94	2.24	10/Ctn/25 kg /1.6'	3
AT-5041	1/2"	5/8	16	7000	320	434	7.48	190	1/4"	3/8"	10.5	297	5.07	2.30	10/Ctn/25 kg /1.6'	3
AT-5043	1/2"	5/8	16	7000	380	515	7.48	190	1/4"	3/8"	13.0	368	6.04	2.74	10/ Ctn/29.5 kg /1.6'	3
AT-5247	1/2"	5/8	16	7000	500	678	7.28	185	1/4"	3/8"	12.0	340	5.73	2.60	8/Ctn/23 kg /1.2'	3

Model No.	AT-5004 / AT-5005	AT-5044K	AT-5648JK / AT-5648TK / AT-5641K
Contents	1 Pc AT-5040 / AT-5041 10 Pcs Air Socket 9,10,11,13,14,17,19,22,24,27 mm 1 Pc 5" Extension Bar 1 Pc Oil Pot 1 Pc Hex. Wrench 1 Pc Nipple 1 Pc Mini Oiler 1 Pc Plastic Case Packing : 4 Sets/Ctn/19 kgs/1.25'	1 Pc AT-5044 10 Pcs Air Socket 9,10,11,13,14,17,19,22,24,27 mm 1 Pc 5" Extension Bar 1 Pc Oil Pot 1 Pc Hex. Wrench 1 Pc Nipple 1 Pc Mini Oiler 1 Pc Plastic Case Packing : 4 Sets/Ctn/19 kgs/1.25'	1 Pc AT-5648J / AT-5648T / AT-5641 10 Pcs Air Socket 10,11,12,13,14,17,19,21,22,24 mm 1 Pc 5" Extension Bar 1 Pc Universal Joint 1 Pc Oil Pot 1 Pc 4mm Hex. Wrench 1 Pc Nipple 1 Pc Mini Oiler 1 Pc Plastic Case Packing : 5 Sets/Ctn/18.9 kgs/1.89'

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)

3/8" IMPACT WRENCH

AT-5238J
3/8" Mini air impact wrench



Handle exhaust

AT-5238T
3/8" Mini air impact wrench



Handle exhaust

AT-5134
3/8" Air impact wrench



Handle exhaust with muffler

AT-5231
3/8" Composite air impact wrench



Handle exhaust with muffler.

AT-5234
3/8" Air impact wrench



Handle exhaust with muffler.

AT-5133
3/8" Air impact wrench



Handle exhaust

AT-5031
3/8" Air impact wrench



Front exhaust

AT-5230
3/8" Air impact wrench



Side exhaust

AT-5130
3/8" Air impact wrench



Side exhaust

AT-5030
3/8" Air impact wrench



Side exhaust

AT-5330
3/8" Air impact wrench



Side exhaust

Model No.	Square Drive	Capacity Bolt Size		Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm		ft-lb	N.m.	inch	mm			scfm	l/min	lb	kg		
AT-5030	3/8"	5/16	8	10000	75	102	6.30	160	1/4"	3/8"	8	226	1.98	0.90	20/Ctn/20 kg /0.7'	2
AT-5031	3/8"	1/2	13	9000	190	258	6.10	155	1/4"	3/8"	10	283	2.53	1.15	16/Ctn/24 kg /1.22'	3
AT-5130	3/8"	3/8	10	9500	125	170	7.09	180	1/4"	3/8"	8.5	241	2.31	1.05	20/Ctn/23 kg /0.9'	3
AT-5133	3/8"	7/16	11	10000	140	190	5.91	150	1/4"	3/8"	8	226	2.97	1.35	10/Ctn/17 kg /1.3	2
AT-5134	3/8"	1/2	13	12000	250	339	5.71	145	1/4"	3/8"	10	283	3.53	1.60	10/Ctn/17.5 kg /0.83'	3
AT-5230	3/8"	5/16	8	10000	100	136	6.10	154	1/4"	5/16"	8	226	1.63	0.74	20/Ctn/17 kg /0.7'	2
AT-5231	3/8"	1/2	12	11000	250	339	6.81	173	1/4"	3/8"	10	283	2.98	1.35	10/Ctn/15 kg /1.26'	3
AT-5234	3/8"	3/8	10	8500	160	217	6.10	155	1/4"	3/8"	7	198	2.91	1.32	12/Ctn/16 kg /1'	2
AT-5238J	3/8"	1/2	12	10000	350	475	4.09	104	1/4"	3/8"	10	283	3.02	1.34	10/Ctn/16 kg /1'	3
AT-5238T	3/8"	1/2	12	10000	350	475	4.09	104	1/4"	3/8"	10	283	3.02	1.34	10/Ctn/16 kg /1'	3
AT-5330	3/8"	3/8	10	9000	160	217	7.95	202	1/4"	3/8"	8	226	2.65	1.20	20/Ctn/28.5 kg /1.1'	2

● Recommended Air Pressure : 90 psi (6.3 kg/cm²)