

1/4" & 3/8" AIR DRILL



AT-4022

2600 rpm 1/4" Composite reversible air drill



AT-4023

2600 rpm 1/4" Composite air drill




AT-4020

4500 rpm 1/4" Air drill




AT-4136

2100 rpm 3/8" Reversible air drill




AT-4135

2100 rpm 3/8" Air drill



AT-4330

2800 rpm 3/8" Air drill



AT-4131

2100 rpm 3/8" Reversible air drill




AT-4131S
2100 rpm 3/8" Reversible air drill
with keyless chuck



AT-4130

2100 rpm 3/8" Air drill



AT-4130S
2100 rpm 3/8" Air drill
with keyless chuck



AT-4331R

2000 rpm 3/8" Reversible air drill



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4020	1/4	6.5	4500	3/8"-24	6.22	158	1/4"	3/8"	8	226	1.50	0.68	20/Ctn/16 kg /1'	3
AT-4022	1/4	6.5	2600	3/8"-24	6.10	155	1/4"	3/8"	8	226	1.19	0.54	20/Ctn/15 kg /1'	3
AT-4023	1/4	6.5	2600	3/8"-24	6.10	155	1/4"	3/8"	8	226	1.19	0.54	20/Ctn/15 kg /1'	3
AT-4130(S)	3/8	10	2100	3/8"-24	7.56	192	1/4"	3/8"	10	283	2.76	1.25	10/Ctn/15kg/0.8'	3
AT-4131(S)	3/8	10	2100	3/8"-24	7.56	192	1/4"	3/8"	10	283	2.76	1.25	10/Ctn/15kg/0.8'	3
AT-4135(S)	3/8	10	2100	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4136(S)	3/8	10	2100	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4237	3/8	10	3000	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4237R	3/8	10	3000	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.87	1.30	10/Ctn/15kg/0.8'	3
AT-4330	3/8	10	2800	3/8"-24	7.87	200	1/4"	3/8"	12	340	2.20	1.00	10/Ctn/12kg/0.8'	3
AT-4331R	3/8	10	2000	3/8"-24	8.46	215	1/4"	3/8"	12	340	2.29	1.04	10/Ctn/12.5kg/0.8'	3
AT-4332	3/8	10	5600	3/8"-24	7.87	200	1/4"	3/8"	12	340	2.09	0.95	10/Ctn/11.5kg/0.8'	3

S : with keyless chuck

3/8" AIR DRILL



AT-4337R
1800rpm 3/8" Reversible air drill
AT-4337RS
1800rpm 3/8" Reversible air drill
with keyless chuck



AT-4337
1800rpm 3/8" Air drill
AT-4337S
1800rpm 3/8" Air drill
with keyless chuck



AT-4337PR
1800rpm 3/8" Reversible air drill
AT-4337PRS
1800rpm 3/8" Reversible air drill
with keyless chuck



AT-4031
1800rpm 3/8" Reversible air drill
AT-4031S
1800rpm 3/8" Reversible air drill
with keyless chuck



AT-4030
1800rpm 3/8" Air drill
AT-4030S
1800rpm 3/8" Air drill
with keyless chuck



AT-4037
4000 rpm 3/8" Air drill
AT-4037S
4000 rpm 3/8" Air drill
with keyless chuck



AT-4038
2500rpm 3/8" Straight air drill
AT-4038S
2500rpm 3/8" Straight air drill
with keyless chuck



AT-4139
3500rpm 3/8" Straight air drill
AT-4139S
3500rpm 3/8" Straight air drill
with keyless chuck



AT-4035
1800rpm 3/8" Angle air drill
AT-4035S
1800rpm 3/8" Angle air drill
with keyless chuck



AT-4036
1700rpm 3/8" Reversible angle air drill
AT-4036S
1700rpm 3/8" Reversible angle air drill
with key less chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4030(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.34	1.06	10/Ctn/13 kg /0.8'	3
AT-4031(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.36	1.07	10/Ctn/13 kg /0.8'	3
AT-4035(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	9	255	2.14	0.97	20/Ctn/23kg /1'	3
AT-4036(S)	3/8	10	1700	3/8"-24	8.46	215	1/4"	3/8"	9	255	2.36	1.07	20/Ctn/25.5 kg /1'	3
AT-4037(S)	3/8	10	4000	3/8"-24	7.68	215	1/4"	3/8"	10	283	2.53	1.15	10/Ctn/13 kg /0.8'	3
AT-4038(S)	3/8	10	2500	3/8"-24	8.46	195	1/4"	3/8"	10.5	297	2.03	0.92	20/Ctn/22 kg /0.85'	3
AT-4139(S)	3/8	10	3500	3/8"-24	8.74	222	1/4"	3/8"	10	283	2.05	0.93	20/Ctn/22 kg /0.85'	3
AT-4337(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.16	0.98	10/Ctn/12 kg /0.8'	3
AT-4337R(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.16	0.98	10/Ctn/12 kg /0.8'	3
AT-4337PR(S)	3/8	10	1800	3/8"-24	7.68	195	1/4"	3/8"	10	283	2.16	0.98	10/Ctn/12 kg /0.8'	3

S : with keyless chuck

1/2" & 5/8" AIR DRILL

AT-4142R 350 rpm
1/2" Reversible air drill
AT-4146 500 rpm
1/2" Reversible air drill
AT-4147R 800 rpm
1/2" Reversible air drill



AT-4141 500 rpm
1/2" Reversible air drill
AT-4141S 500 rpm
1/2" Reversible air drill
with keyless chuck



AT-4041 800 rpm
1/2" reversible air drill
AT-4041S 800 rpm
1/2" reversible air drill
with keyless chuck



AT-4347R 800 rpm
1/2" Reversible air drill
AT-4347RS 800 rpm
1/2" Reversible air drill
with keyless chuck



AT-4142
350 rpm 1/2" Air drill
AT-4145
500 rpm 1/2" Air drill
AT-4147
800 rpm 1/2" Air drill



AT-4140
500 rpm 1/2" Air drill
AT-4140S
500 rpm 1/2" Air drill
with keyless chuck



AT-4040
800 rpm 1/2" Air drill
AT-4040S
800 rpm 1/2" Air drill
with keyless chuck



AT-4347
800 rpm 1/2" Air drill
AT-4347S
800 rpm 1/2" Air drill
with keyless chuck



AT-4049 1000 rpm
5/8" Reversible air drill



AT-4341R
700 rpm 1/2" Reversible
air drill-0.6hp



AT-4340
700 rpm 1/2" air drill-0.6hp



AT-4347PR 800 rpm
1/2" Reversible air drill
AT-4347PRS 800 rpm
1/2" Reversible air drill
with keyless chuck



SPECIFICATIONS (at 90psi-6.2bar)

Model No.	Chuck Size		Free Speed RPM	Spindle	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			inch	mm			scfm	l/min	lb	kg		
AT-4040(S)	1/2	13	800	3/8"-24	8.74	222	1/4"	3/8"	10	283	3.26	1.48	10/Ctn/18kg/1.32'	3
AT-4041(S)	1/2	13	800	3/8"-24	8.98	228	1/4"	3/8"	10	283	3.37	1.53	10/Ctn/18kg/1.32'	3
AT-4049	5/8	16	1000	--	16.14	410	3/8"	1/2"	19	538	13.70	6.22	4/Ctn/26kg /1.5'	5
AT-4140(S)	1/2	13	500	3/8"-24	8.86	225	1/4"	3/8"	10	283	3.96	1.80	10/Ctn/20kg/1.32'	3
AT-4141(S)	1/2	13	500	3/8"-24	8.86	225	1/4"	3/8"	10	283	3.96	1.80	10/Ctn/20kg/1.32'	3
AT-4142(S)	1/2	13	350	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/1.32'	3
AT-4142R(S)	1/2	13	350	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/1.32'	3
AT-4145(S)	1/2	13	500	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/1.32'	3
AT-4146(S)	1/2	13	500	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/1.32'	3
AT-4147(S)	1/2	13	800	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.90	1.77	10/Ctn/20kg/1.32'	3
AT-4147R(S)	1/2	13	800	3/8"-24	9.13	232	1/4"	3/8"	10	283	3.88	1.76	10/Ctn/20kg/1.32'	3
AT-4340	1/2	13	700	1/2"-20	9.45	240	1/4"	3/8"	12	340	3.09	1.40	10/Ctn/17kg/1.32'	3
AT-4341R	1/2	13	700	1/2"-20	9.92	252	1/4"	3/8"	12	340	3.09	1.40	10/Ctn/17kg/1.32'	3
AT-4347 (S)	1/2	13	800	3/8"-24	8.90	226	1/4"	3/8"	10	283	3.17	1.44	10/Ctn/18kg/1.32'	3
AT-4347R (S)	1/2	13	800	3/8"-24	8.90	226	1/4"	3/8"	10	283	3.17	1.44	10/Ctn/18kg/1.32'	3
AT-4347PR (S)	1/2	13	800	3/8"-24	8.90	226	1/4"	3/8"	10	283	3.17	1.44	10/Ctn/18kg/1.32'	3

S : with keyless chuck