

INDUSTRIAL AIR ANGLE GRINDER / VERTICAL GRINDER

AT-7056
2" Angle grinder
AT-7056R
2" Angle grinder (roll type throttle)



AT-7042
4" Angle grinder
AT-7042R
4" Angle grinder (roll type throttle)



AT-7043
5" Angle grinder
AT-7043R
5" Angle grinder (roll type throttle)



AT-7044
7" Angle grinder
AT-7044R
7" Angle grinder (roll type throttle)



AT-7045
9" Angle grinder
AT-7045R
9" Angle grinder (roll type throttle)



AT-7055
6" Air vertical cup wheel grinder



AT-7151
7" Turbine angle grinder



AT-7052
5" Air vertical grinder
AT-7053
7" Air vertical grinder



AT-7054
9" Air vertical grinder



Model No.	Free Speed RPM	Grinding Wheel Size		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
		inch	mm	inch	mm			scfm	l/min	lb	kg		
AT-7042	13000	4	100	9.70	246	1/4"	3/8"	15	425	4.01	1.82	10/Ctn/25 kg/2.37'	5
AT-7042R	13000	4	100	8.20	208	1/4"	3/8"	15	425	3.77	1.71	10/Ctn/25 kg/2.37'	5
AT-7043	10900	5	125	9.70	246	1/4"	3/8"	15	425	4.10	1.86	10/Ctn/26 kg/2.37'	5
AT-7043R	10900	5	125	8.20	208	1/4"	3/8"	15	425	3.86	1.76	10/Ctn/26 kg/2.37'	5
AT-7044	7600	7	180	11.80	330	3/8"	1/2"	20	566	7.32	3.32	6/Ctn/27 kg/3.13'	7.5
AT-7044R	7600	7	180	10.00	253	3/8"	1/2"	20	566	6.80	3.10	6/Ctn/27 kg/3.13'	7.5
AT-7045	5900	9	230	13.00	330	3/8"	1/2"	25	708	8.82	4.00	4/Ctn/21.7 kg/2.34'	7.5
AT-7045R	5900	9	230	11.22	285	3/8"	1/2"	25	708	8.38	3.80	4/Ctn/21.7 kg/2.34'	7.5
AT-7052	12000	5	125	9.40	240	3/8"	1/2"	24	679	6.80	3.10	6/Ctn/24.1 kg/2.8'	7.5
AT-7053	8400	7	180	10.20	260	3/8"	1/2"	28	792	9.70	4.40	4/Ctn/22 kg/2.5'	7.5
AT-7054	6000	9	230	11.00	279	1/2"	3/4"	35	889	13.70	6.20	4/Ctn/30 kg/2.6'	10
AT-7055	4500	6	150	7.40	188	1/2"	3/4"	35	889	13.00	5.90	4/Ctn/30 kg/2.6'	10
AT-7056	15000	2	50	7.68	195	1/4"	3/8"	7.5	212	1.63	0.74	10/Ctn/10 kg/0.92'	3
AT-7056R	15000	2	50	6.20	157	1/4"	3/8"	7.5	212	1.41	0.66	10/Ctn/10 kg/0.92'	3
AT-7151	8500	7	180	12.4	310	1/4"	3/4"	60	1698	8.40	3.80	10/Ctn/4.5 kg/0.8'	20

R : Roll type throttle

AIR ANGLE GRINDER / STRAIGHT GRINDER

AT-7144
4" 120° Angle grinder



AT-7145
5" 120° Angle grinder



AT-7036
4" Angle grinder (safety lever)
AT-7036R
4" Angle grinder (roll type throttle)



AT-7037
5" Angle grinder (safety lever)
AT-7037R
5" Angle grinder (roll type throttle)



AT-7049
2" Angle grinder (side exhaust)



AT-7048
4" Angle grinder (safety lever)
AT-7048R
4" Angle grinder (roll type throttle)



AT-7050
4" Angle grinder (safety lever)
AT-7050R
4" Angle grinder (roll type throttle)
AT-7051
5" Angle grinder (safety lever)
AT-7051R
5" Angle grinder (roll type throttle)



AT-7041
7" Air grinder



AT-7158
Cone wheel grinder



Part No.	Dia A	Length B	Hole C	MAX. RPM
GS-20	45mm	75mm	5/8"-11	14000

AT-7157
3" Straight grinder



AT-7058
5" Straight grinder



AT-7059
6" Straight grinder



Model No.	Free Speed RPM	Spindle Thread	Grinding wheel Size		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm	inch	mm			scfm	l/min	lb	kg		
AT-7036	11000	3/8"-24UNF	4	100	9.06	230	1/4"	3/8"	12.0	340	3.88	1.76	10/Ctn/22.1 kg/1.43'	3
AT-7036R	11000	3/8"-24UNF	4	100	8.86	225	1/4"	3/8"	12.0	340	4.08	1.85	10/Ctn/22.9 kg/1.43'	3
AT-7037	11000	3/8"-24UNF	5	125	9.06	230	1/4"	3/8"	12.0	340	3.92	1.78	10/Ctn/22.5 kg/1.43'	3
AT-7037R	11000	3/8"-24UNF	5	125	8.86	225	1/4"	3/8"	12.0	340	4.12	1.87	10/Ctn/23.3 kg/1.43'	3
AT-7041	7000	--	7	180	13.39	340	3/8"	3/8"	16.5	467	7.05	3.20	6/Ctn/24.5 kg/2.5'	7.5
AT-7048	13000	M8 x P1.25	4	100	7.09	180	1/4"	3/8"	9.0	255	2.12	0.96	10/Ctn/13.2 kg/1.3'	3
AT-7048R	13000	M8 x P1.25	4	100	7.09	180	1/4"	3/8"	9.0	255	2.12	0.96	10/Ctn/12 kg/1.2'	3
AT-7049	22000	M6 x P1.0	2	50	5.51	140	1/4"	3/8"	8.0	226	1.17	0.53	20/Ctn/13.5 kg/1.5'	3
AT-7050	12000	M8 x P1.25	4	100	8.66	220	1/4"	3/8"	11.5	325	3.53	1.60	10/Ctn/16 kg/1.4'	3
AT-7050R	12000	M8 x P1.25	4	100	8.66	220	1/4"	3/8"	11.5	325	3.53	1.60	10/Ctn/16 kg/1.4'	3
AT-7051	12000	M8 x P1.25	5	125	8.66	220	1/4"	3/8"	11.5	325	3.53	1.60	10/Ctn/16 kg/1.4'	3
AT-7051R	12000	M8 x P1.25	5	125	8.66	220	1/4"	3/8"	11.5	325	3.53	1.60	10/Ctn/16 kg/1.4'	3
AT-7144	9300	M10 x 1.5P	4	100	10.20	260	1/4"	3/8"	9.0	255	3.42	1.55	10/Ctn/20 kg/1.8'	3
AT-7145	9300	M14 x 2.0P	5	125	10.40	265	1/4"	3/8"	9.0	255	3.53	1.60	10/Ctn/20.5 kg/1.8'	3
AT-7058	7600	1/2"-12	5	125	19.70	501	3/8"	1/2"	20.0	566	6.55	2.97	4/Ctn/15kg/1.7'	5
AT-7059	6900	5/8"-11	6	150	20.50	521	3/8"	1/2"	24.0	679	9.13	4.14	4/Ctn/20.6kg/1.7'	7.5
AT-7157	14600	3/8"-16	3	75	15.40	390	3/8"	3/8"	15.0	425	3.80	1.72	10/Ctn/19kg/1.6'	5
AT-7158	6900	5/8"-11	1.77	45	20.10	510	3/8"	1/2"	24.0	679	7.27	3.30	6/Ctn/21kg/1.0'	7.5

R : Roll type throttle