

SAND RAMMER

AT-2402
Sand rammer



AT-2403
Sand rammer



AT-2404
Sand rammer



AT-2403L
Sand rammer



AT-2404L
Sand rammer



AT-2405L
Sand rammer



Model No.	Piston Diameter		Piston Stroke		Blow per min. (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Work Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm	inch	mm		inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-2402	0.71	18.0	2.0	50	1500	11~14.2	280~360	1/4"	3/8"	6	170	3.53	1.60	90	6.3	10/Ctn/20 kg/0.76'	2
AT-2403	0.87	22.0	2.6	65	1000	15~18.5	380~470	3/8"	3/8"	8	226	6.50	2.95	90	6.3	6/Ctn/14.2 kg/1.39'	3
AT-2403L	0.87	22.0	2.6	65	1000	34.3~38.6	870~980	3/8"	3/8"	8	226	8.27	3.75	90	6.3	6/Ctn/25 kg/1.39'	3
AT-2404	1.00	25.4	4.0	100	800	19.7~26	500~660	3/8"	3/8"	12	340	13.22	6.00	90	6.3	4/Ctn/31.2 kg/1.6'	3
AT-2404L	1.00	25.4	4.0	100	800	41.7~47.6	1060~1210	1/2"	1/2"	12	340	17.63	8.00	90	6.3	2/Ctn/17.3 kg/1.08'	3
AT-2405L	1.26	32.0	5.0	125	700	42.5~49.2	1080~1250	1/2"	1/2"	16	453	21.58	9.79	90	6.3	2/Ctn/20.7 kg/1.08'	5