

AT-6069A
Turbo lap linear (stroke:0.3mm)



AT-6069B
Turbo lap linear (stroke:0.7mm)



AT-6069C
Turbo lap linear (stroke:1.2mm)



AT-6070A
Turbo lap swing (stroke:0.3mm)



AT-6070B
Turbo lap swing (stroke:0.7mm)



AT-6070C
Turbo lap swing (stroke:1.2mm)



AT-6066
Vibration reduced super fine air lapper



AT-6067
Vibration reduced finishing air file



AT-6068
Vibration reduced air file



Model No.	Shank Size (mm)	Stroke Length (mm)	Stroke Per Minute (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Hose Ass'y Length (M)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
				inch	mm				scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6066	Ø3	0.5~1	21000	8.07	205	1/4"	1/4"	1.5	6	170	1.19	0.54	90	6.3	20/Ctn/16 kg/1.85'	2
AT-6067	Ø5	3~5	12000	8.07	205	1/4"	1/4"	1.5	5	142	1.19	0.54	90	6.3	20/Ctn/16.6 kg/1.85'	2
AT-6068	Ø5	7~10	10000	7.87	200	1/4"	1/4"	1.5	4	113	1.41	0.64	90	6.3	20/Ctn/19.7 kg/1.85'	2
AT-6069A	Ø3	0.3	50000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2
AT-6069B	Ø3	0.7	22000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2
AT-6069C	Ø3	1.2	15000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2
AT-6070A	Ø3	0.3	50000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2
AT-6070B	Ø3	0.7	22000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2
AT-6070C	Ø3	1.2	15000	8.27	210	1/4"	1/4"	1.5	4	113	0.42	0.19	90	6.3	38/Ctn/18 kg/2.19'	2



AT-6214

Vibration reduced industrial air saw



Front exhaust



AT-6210

Gear driven air saw



Rear exhaust
360 exhaust diffuser



AT-6209

Gear driven air saw



Rear exhaust



AT-6211

2 in 1 Air body saw



Rear exhaust
360 exhaust diffuser



AT-6207

Gear driven air saw



Rear exhaust



AT-6110

Vibration reduced air body saw



Front exhaust



AT-6011

Air body saw



Front exhaust



AT-6008

Air body saw



Rear exhaust
360 exhaust diffuser



AT-6113

Vibration reduced air pipe saw



Front exhaust

Model No.	Cutting Capacity (mm)		Stroke Length (mm)	Stroke Per Minute (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Steel	Alum.			inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6008	1.6	2.5	10	9000	9.25	235	1/4"	3/8"	5.0	142	1.54	0.70	90	6.3	20/Ctn/16 kg/1.0'	2
AT-6011	1.6	2.5	10	10000	9.06	230	1/4"	3/8"	5.0	142	1.37	0.62	90	6.3	20/Ctn/16.6 kg/1.0'	2
AT-6110	2.9	3.3	10	10000	10.35	263	1/4"	3/8"	4.5	127	1.12	0.51	90	6.3	20/Ctn/16 kg/1.17'	2
AT-6113	5.0	8.0	25	5000	13.58	345	1/4"	3/8"	4.5	127	1.68	0.76	90	6.3	10/Ctn/13 kg/1.45'	2
AT-6207	1.6	2.5	10	6000	9.06	230	1/4"	3/8"	7.0	198	1.76	0.80	90	6.3	20/Ctn/18 kg/1.2'	3
AT-6209	2.0	3.0	6	10000	7.76	197	1/4"	3/8"	8.0	226	1.25	0.58	90	6.3	20/Ctn/14 kg/1.0'	3
AT-6210	5.0	8.0	10	7000	12.20	310	1/4"	3/8"	10.0	283	2.64	1.20	90	6.3	10/Ctn/14 kg/0.9'	3
AT-6211	3.0	3.7	10	9000	9.25	235	1/4"	3/8"	5.0	142	1.54	0.70	90	6.3	20/Ctn/16 kg/1.0'	2
AT-6214	20.0	25.0	45	1200	15.75	400	1/4"	3/8"	8.0	226	6.17	2.80	90	6.3	5/Ctn/18 kg/1.44'	3

CUT-OFF TOOL / NIBBLER

AT-6220
3" Air cut-off tool



AT-6221
4" Air cut-off tool



AT-6222
4.5" Air cut-off tool



AT-6027
Air cut off tool



AT-6126
3" Air cut-off tool



AT-6127
4" Air cut-off tool



AT-6128
4" Air mini circular saw



AT-6025
Air nibbler (push type)



AT-6123
Air nibbler (pull type)



Model No.	Cutting Wheel Dia.		Free Speed (RPM)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm		inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6027	3x1/16x3/8	75x1.6x9.5	20000	9.36	187	1/4"	3/8"	10	283	1.72	0.78	90	6.3	20/Ctn/18 kg /1.34'	2
AT-6126	3x1/16x3/8	75x1.6x9.5	20000	7.09	180	1/4"	3/8"	10	283	1.85	0.84	90	6.3	10/Ctn/10 kg /1.0'	2
AT-6127	4x1/16x3/8	100x1.6x9.5	15000	16.7	420	1/4"	3/8"	10	283	3.70	1.68	90	6.3	10/Ctn/18 kg /1.7'	2
AT-6128	4x5/64x51/64	100x2x20	8000	9.37	238	1/4"	3/8"	9	255	2.71	1.23	90	6.3	10/Ctn/17 kg /2.0'	2
AT-6220	3x1/16x3/8	75x1.6x9.5	18000	8.86	225	1/4"	3/8"	10	283	1.83	0.83	90	6.3	20/Ctn/18 kg /1.4'	2
AT-6221	4x1/16x3/8	100x1.6x9.5	13000	9.45	240	1/4"	3/8"	12	340	2.05	0.93	90	6.3	20/Ctn/19.6 kg /2.0'	3
AT-6222	4.5x1/16x7/8	115x1.6x22.2	13000	9.45	240	1/4"	3/8"	12	340	2.05	0.93	90	6.3	20/Ctn/19.6 kg /2.0'	3

Model No.	Cutting Capacity (mm)		Stroke Per Minute (B.P.M.)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Steel	Alum.		inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6025	1.4	1.6	2900	7.09	180	1/4"	3/8"	9.5	269	2.16	0.98	90	6.3	20/Ctn/21 kg/1'	2
AT-6123	1.4	1.6	3500	7.68	195	1/4"	3/8"	10	283	2.05	0.93	90	6.3	20/Ctn/21 kg/1.2'	2

AIR METAL SHEAR / AIR KNIFE

AT-6225
Composite Air metal shear



AT-6021
Air metal shear



AT-6226
Air metal shear



AT-6223
Composite Air scissor shear



AT-6023
Air scissor shear



AT-6224
Air scissor shear



AT-6125
2 in 1 Oscillating multi-tool



AT-6014
Air knife



AT-6014K
Air knife kit



Contents :
1 pc AT-6014
1 pc 5mm hex. Wrench
3 pcs Knife blades
1 Pc Plastic Case
Packing : 10/Ctn/18.2 kg /1.4'

Model No.	Cutting Capacity (mm)		Width Of Cut (mm)	Free Speed (RPM)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	Steel	Alum.			inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6021	1.2	1.4	5.6	2000	8.46	215	1/4"	3/8"	7	198	2.51	1.14	90	6.3	10/Ctn/13.5 kg/1.06'	2
AT-6023	1.2	1.4	5.6	2000	10.00	255	1/4"	3/8"	8	226	3.03	1.35	90	6.3	10/Ctn/16.5 kg/1.44'	2
AT-6223	1.2	1.4	-	2000	10.04	264	1/4"	3/8"	8	226	2.64	1.20	90	6.3	10/Ctn/14 kg/1.06'	2
AT-6224	1.2	1.4	-	2500	11.70	297	1/4"	3/8"	10	283	2.64	1.20	90	6.3	10/Ctn/14 kg/1.44'	2
AT-6225	1.2	1.4	5.6	2000	8.86	225	1/4"	3/8"	8	226	2.58	1.17	90	6.3	10/Ctn/13.5 kg/1.06'	2
AT-6226	1.2	1.4	5.6	2500	10.20	259	1/4"	3/8"	10	283	2.47	1.12	90	6.3	20/Ctn/24 kg/0.85'	2

Model No.	knife Oscillation (per/min.)	Cutting Distance (mm)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
			inch	mm			scfm	l/min	lb	kg	psi	kg/cm ²		
AT-6014	20000	3	7.87	200	1/4"	3/8"	8	226	2.34	1.06	90	6.3	10/Ctn/16 kg /1.4'	2
AT-6125	20000	3	7.09	180	1/4"	3/8"	8	226	1.50	0.68	90	6.3	20/Ctn/15.5 kg /1'	2

AIR NIPPER

AT-6072
Air nipper



AT-6073
Air nipper



AT-6074
Air nipper



AT-6075
Air nipper



AT-6076
Air nipper



AT-6174
Air nipper



AT-6175
Air nipper



AT-6176
Air nipper



Wire Cutting Blade



Blade Model	Capacity (mm)				For Tools
	Copper Wire	Iron Wire	Stainless Wire	Piano Wire	
TP-6072	Ø1.0	Ø0.5	x	x	AT-6072
TP-6073	Ø1.6	Ø1.0	x	x	AT-6073
TP-6074	Ø2.6	Ø2.0	x	x	AT-6074 AT-6174
TP-6075	Ø3.3 Ø4.8	Ø2.8 Ø4.0	x	x	AT-6075 AT-6175 AT-6076 AT-6176

Carbide Tipped Blade




Blade Model	Capacity (mm)				For Tools
	Copper Wire	Iron Wire	Stainless Wire	Piano Wire	
TP-6072Z	Ø1.0	Ø0.5	x	Ø 0.3	AT-6072
TP-6073Z	Ø1.6	Ø1.0	x	Ø 0.5	AT-6073
TP-6074Z	Ø2.6	Ø2.0	x	Ø 1.0	AT-6074 AT-6174
TP-6075Z	Ø3.3 Ø4.8	Ø2.8 Ø4.0	2.0 2.8	Ø 1.2 Ø 1.2	AT-6075 AT-6175 AT-6076 AT-6176

Non-insulated Terminal Crimping Blade



Blade Model	Capacity (mm)	Size		For Tools
		A (mm)	B (mm)	
TP-6074A5P	1.25 sq	11.0	5.7	AT-6074 AT-6174
TP-6075A7PA	1.25 sq	11.5	6.5	AT-6075 AT-6175
TP-6075A7PB	2.0 sq	11.5	6.5	AT-6075 AT-6175
TP-6075A7PC	5.5 sq	11.5	6.5	AT-6075 AT-6175
TP-6075A7WP-3	1.25~5.5 sq	28.0	6.0	AT-6075 AT-6175
TP-6076A7P	8.0 sq	11.5	6.5	AT-6076 AT-6176

Insulated Terminal Crimping Blade



Blade Model	Capacity (mm)	Size		For Tools
		A (mm)	B (mm)	
TP-6075AR7PA	1.25 sq	17	6	AT-6075
TP-6075AR7PB	2.0 sq	17	6	AT-6075
TP-6075AR7PC	5.5 sq	17	6	AT-6075
TP-6075AR7WP	2.0~5.5 sq	22	5.8	AT-6075
TP-6076AR7P	8.0 sq	17	6	AT-6076

Model No.	Cutting Capacity (mm)		Body Dia. (mm)	Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption l/cycle	Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	copper	iron		inch	mm				lb	kg	psi	kg/cm ²		
AT-6072	Ø1.0	Ø0.5	30	4.72	120	1/4"	3/16"	0.06	0.37	0.17	57-70	4-5	30/Ctn/10 kg /0.9'	1
AT-6073	Ø1.6	Ø1.0	36	5.35	136	1/4"	3/16"	0.12	0.58	0.26	70-85	5-6	30/Ctn/12 kg /0.9'	1
AT-6074	Ø2.6	Ø2.0	45	6.69	170	1/4"	3/16"	0.23	0.75	0.34	70-85	5-6	20/Ctn/11 kg /0.9'	1
AT-6075	Ø3.3	Ø2.8	56	8.15	207	1/4"	3/16"	0.58	1.23	0.56	70-85	5-6	20/Ctn/15 kg /0.9'	1
AT-6076	Ø4.8	Ø4.0	56	13.3	337	1/4"	3/16"	0.96	2.78	1.26	70-85	5-6	10/Ctn/14 kg /0.9'	1
AT-6174	Ø2.6	Ø2.0	45	7.28	185	1/4"	3/16"	0.23	1.06	0.48	70-85	5-6	20/Ctn/11 kg /0.9'	1
AT-6175	Ø3.3	Ø2.8	56	9.10	231	1/4"	3/16"	0.58	2.07	0.94	70-85	5-6	20/Ctn/21 kg /0.9'	1
AT-6176	Ø4.8	Ø4.0	56	12.8	324	1/4"	3/16"	0.96	2.82	1.28	70-85	5-6	10/Ctn/14 kg /0.9'	1